TP-LINK

TL-SG1016D

Kod: 00-00001578 · Switchlər



TP-LINK TL-SG1016D 16 portlu gigabit switch ilə sürətli və etibarlı şəbəkə bağlantısı təmin edin – masaüstü və rackmont quruluşları ilə ofis və kiçik biznes şəbəkələri üçün mükəmməl seçim.

Texniki göstəricilər

16 Port
Port sayı

1000mb/s
Port sürəti

Ətraflı məlumat

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab , IEEE 802.3x
Interface	16 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Physical Security Lock	No
Power Supply	100-240VAC, 50/60Hz
Dimensions (W x D x H)	11.6 × 5.5 × 1.7 in. (294 × 140 × 44 mm)
Max. Power Consumption	10.68 W (220 V/50 Hz)
Max Heat Dissipation	36.31 BTU/h
PERFORMANCE	
Switching Capacity	32Gbps
Packet Forwarding Rate	23.8Mpps
MAC Address Table	8K
Advanced Features	Isolation Mode: Ports 1-14 Loop Prevention: Ports 1-16
Jumbo Frame	10KB
Green Technology	Yes
Transmission Method	Store-and-Forward
OTHERS	
Certification	FCC, CE, RoHs
Package Content	16-Port Gigabit Desktop/Rackmount Switch Power Cord Installation Guide Rackmount Kits Rubber Feet

Environment	Operating Temperature: 0℃~40℃ (32℉~104℉); Storage Temperature: -40℃~70℃ (-40℉~158℉); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az