

TP-LINK

TL-SG1024D

Kod: 00-00000543 · Switchlər



TP-LINK TL-SG1024D 24 portlu gigabit switch ilə sürətli və etibarlı şəbəkə bağlantısı əldə edin – masaüstü və rackmont quruluşları ilə ofis və biznes şəbəkələri üçün ideal seçim

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](https://eurotechnology.az/product/tp-link/tl-sg1024d)
<https://eurotechnology.az/product/tp-link/tl-sg1024d>

Texniki göstəricilər



24 Port

Port sayı



1000mb/s

Port sürəti

Ətraflı məlumat

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab , IEEE 802.3x
Interface	24 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Physical Security Lock	No
Power Supply	100-240VAC, 50/60Hz
Dimensions (W x D x H)	11.6 × 5.5 × 1.7 in (294 × 140 × 44 mm)
Mounting	Rack Mountable
Max Power Consumption	13.62W(220V/50Hz)
Max Heat Dissipation	46.44BTU/h
PERFORMANCE	
Switching Capacity	48Gbps
Packet Forwarding Rate	35.7Mpps
MAC Address Table	8K
Advanced Functions	• Isolation Mode: Ports 1-22 • Loop Prevention: Ports 1-24
Jumbo Frame	10KB
Green Technology	Yes
Transfer Method	Store-and-Forward
OTHERS	
Certification	FCC, CE, RoHS
Package Contents	24-Port Gigabit Desktop/Rackmount Switch Power Cord Installation Guide Rackmount Kits Rubber Feet

Environment

Operating Temperature: 0°C~40°C (32°F~104°F);

Storage Temperature: -40°C~70°C (-40°F~158°F);

Operating Humidity: 10%~90% non-condensing;

Storage Humidity: 5%~90% non-condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az