

TP-LINK

TL-SG3428MP

Kod: 00-00005474 · Switchlər



TP-Link TL-SG3428MP Omada 28 portlu Gigabit L2+ idarəolunan switchdir. 24 PoE+ portu IP kameralar, access pointlər və VoIP üçün yüksək PoE gücü təmin edir. 4 SFP uplink, VLAN, QoS, ACL və Omada SDN mərkəzləşdirilmiş idarəetmə dəstəyi ilə biznes və enterprise şəbəkələri üçün ideal həldir.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)<https://eurotechnology.az/product/tp-link/tl-sg3428mp>

Texniki göstəricilər

**24 Port**

Port sayı

**Managed**

Tip

**PoE+**

PoE

**1000mb/s**

Port sürəti

**400 W**

PoE gücü

Ətraflı məlumat

HARDWARE FEATURES	
Interface	• 24× 10/100/1000Mbps RJ45 Ports • 4× Gigabit SFP Slots • 1× RJ45 Console Port • 1× Micro-USB Console Port
Fan Quantity	2
Power Supply	100-240 V AC~50/60 Hz
PoE Ports (RJ45)	• Standard: 802.3at/af compliant • PoE+ Ports: 24 Ports, up to 30 W per port • Power Budget: 384 W*
Dimensions (W x D x H)	17.3 × 13.0 × 1.7 in (440 × 330 × 44 mm)
Mounting	Rack Mountable
Max Power Consumption	• V1: 463.8 W (110 V/60 Hz) (with 384 W PD connected); 31.0 W (110 V/60 Hz) (no PD connected) • V2: 465.8 W (110 V/60 Hz) (with 384 W PD connected); 34.4 W (110 V/60 Hz) (no PD connected) • V3: 442.1 W (220 V/50 Hz) (with 384 W PD connected) • V4: 460.8 W (110 V/60 Hz) (with 384 W PD connected) • V5: 456.4 W (110 V/60 Hz) (with 384 W PD connected)
Max Heat Dissipation	• V1: 1582.49 BTU/h (110 V/60 Hz) (with 384 W PD connected); 105.78 BTU/h (110 V/60 Hz) (no PD connected) • V2: 1589.31 BTU/hr (110 V/60 Hz) (with 384 W PD connected); 117.38 BTU/hr (110 V/60 Hz) (no PD connected) • V3: 1508.67 BTU/hr (220 V/50 Hz) (with 384 W PD connected) • V4: 1572.48 BTU/hr (110 V/60 Hz) (with 384 W PD connected) • V5: 1557.47 BTU/hr (110 V/60 Hz) (with 384 W PD connected)
PERFORMANCE	
Switching Capacity	56 Gbps
Packet Forwarding Rate	41.66 Mpps
MAC Address Table	• V1: 8K • V2 and above: 16K

HARDWARE FEATURES	
Packet Buffer Memory	4.1 Mbit
Jumbo Frame	9 KB
SOFTWARE FEATURES	
Quality of Service	• 8 priority queues • 802.1p CoS/DSCP priority • Queue scheduling - SP (Strict Priority) - WRR (Weighted Round Robin) - SP+WRR • Bandwidth Control - Port/Flow based Rating Limiting • Smoother Performance • Action for Flows - Mirror (to supported interface) - Redirect (to supported interface) - Rate Limit - QoS Remark
L3 Features	• 16 IPv4/IPv6 Interfaces • Static Routing - 48 static routes • Static ARP - 128 static entries • 316 ARP Entries (512 ARP Entries for TL-SG3428 V2.0 & TL-SG3428MP V2.0) • Proxy ARP • Gratuitous ARP • DHCP Server • DHCP Relay - DHCP interface relay - DHCP VLAN relay • DHCP L2 Relay

HARDWARE FEATURES
L2 and L2+ Features

- Link Aggregation
 - Static link aggregation
 - 802.3ad LACP
 - Up to 8 aggregation groups and up to 8 ports per group
- Spanning Tree Protocol
 - 802.1d STP
 - 802.1w RSTP
 - 802.1s MSTP
 - STP Security: TC Protect, BPDU Filter, BPDU Protect, Root Protect, Loop Protect
- Loopback Detection
 - Port-based
 - VLAN based
- Flow Control
 - 802.3x Flow Control
 - HOL Blocking Prevention
- Mirroring
 - Port Mirroring
 - CPU Mirroring
 - One-to-One
 - Many-to-One
 - Tx/Rx/Both

L2 Multicast

- Supports 511 (IPv4, IPv6) IGMP groups
- IGMP Snooping
 - IGMP v1/v2/v3 Snooping
 - Fast Leave
 - IGMP Snooping Querier
 - IGMP Authentication
- IGMP Authentication
- MVR
- MLD Snooping
 - MLD v1/v2 Snooping
 - Fast Leave
 - MLD Snooping Querier
 - Static Group Config
 - Limited IP Multicast
- Multicast Filtering: 256 profiles and 16 entries per profile

HARDWARE FEATURES	
Advanced Features	• Automatic Device Discovery • Batch Configuration • Batch Firmware Upgrading • Intelligent Network Monitoring • Abnormal Event Warnings • Unified Configuration • Reboot Schedule
VLAN	• VLAN Group - Max 4K VLAN Groups • 802.1Q Tagged VLAN • MAC VLAN: 12 Entries (30 Entries for TL-SG3428 V2.0 & TL-SG3428MP V2.0) • Protocol VLAN: Protocol Template 16, Protocol VLAN 16 • Private VLAN • GVRP • VLAN VPN (QinQ) - Port-Based QinQ - Selective QinQ • Voice VLAN

HARDWARE FEATURES**Access Control List**

- Time-based ACL
- MAC ACL
 - Source MAC
 - Destination MAC
 - VLAN ID
 - User Priority
 - Ether Type
- IP ACL
 - Source IP
 - Destination IP
 - Fragment
 - IP Protocol
 - TCP Flag
 - TCP/UDP Port
 - DSCP/IP TOS
 - User Priority
- Combined ACL
- Packet Content ACL
- IPv6 ACL
- Policy
 - Mirroring
 - Redirect
 - Rate Limit
 - QoS Remark
- ACL apply to Port/VLAN

HARDWARE FEATURES
Security

- IP-MAC-Port Binding
- DHCP Snooping
- ARP Inspection
- IPv4 Source Guard
- IPv6-MAC-Port Binding
- DHCPv6 Snooping
- ND Detection
- IPv6 Source Guard
- DoS Defend
- Static/Dynamic Port Security
- Up to 64 MAC addresses per port
- Broadcast/Multicast/Unicast Storm Control
- kbps/ratio/pps control mode
- IP/Port/MAC based access control
- 802.1X
- Port based authentication
- Mac based authentication
- VLAN Assignment
- MAB
- Guest VLAN
- Support Radius authentication and accountability
- AAA (including TACACS+)
- Port Isolation
- Secure web management through HTTPS with SSLv3/TLS 1.2
- Secure Command Line Interface (CLI) management with SSHv1/SSHv2

HARDWARE FEATURES	
IPv6	• IPv6 Dual IPv4/IPv6 • Multicast Listener Discovery (MLD) Snooping • IPv6 ACL • IPv6 Interface • Static IPv6 Routing • IPv6 neighbor discovery (ND) • Path maximum transmission unit (MTU) discovery • Internet Control Message Protocol (ICMP) version 6 • TCPv6/UDPv6 • IPv6 applications - DHCPv6 Client - Ping6 - Tracert6 - Telnet (v6) - IPv6 SNMP - IPv6 SSH - IPv6 SSL - Http/Https - IPv6 TFTP
MIBs	• MIB II (RFC1213) • Bridge MIB (RFC1493) • P/Q-Bridge MIB (RFC2674) • Radius Accounting Client MIB (RFC2620) • Radius Authentication Client MIB (RFC2618) • Remote Ping, Traceroute MIB (RFC2925) • Support TP-Link private MIBs • RMON MIB(RFC1757, rmon 1,2,3,9)
MANAGEMENT	
Omada App	Yes, through • Omada Cloud-Based Controller (Not Supported by TL-SG3428MP v3) • OC300 • OC200 • Omada Software Controller
Centralized Management	• Omada Cloud-Based Controller (Not Supported by TL-SG3428MP v3) • Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller

HARDWARE FEATURES	
Cloud Access	Yes, through • Omada Cloud-Based Controller (Not Supported by TL-SG3428MP v3) • OC300 • OC200 • Omada Software Controller
Zero-Touch Provisioning	Yes. Requiring the use of Omada Cloud-Based Controller (Supported by TL-SG3428MP v1, v2, v4 and above, while is not supported by TL-SG3428MP v3)
Management Features	• Web-based GUI • Command Line Interface (CLI) through console port, telnet • SNMPv1/v2c/v3 - Trap/Inform - RMON (1, 2, 3, 9 groups) • SDM Template • DHCP/BOOTP Client • 802.1ab LLDP/LLDP-MED • DHCP AutoInstall • Dual Image, Dual Configuration • CPU Monitoring • Cable Diagnostics • EEE • Password Recovery • SNTP • System Log
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	• TL-SG3428MP Switch • Power Cord • Quick Installation Guide • Rackmount Kit • Rubber Feet
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7/8/10/11, MAC® OS, NetWare®, UNIX® or Linux.
Environment	• Operating Temperature: 0-45 °C (32-113 °F); • Storage Temperature: -40-70 °C (-40-158 °F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az