


TP-LINK

TL-SG3452P

Kod: 00-00003966 · Switchlər



TP-Link TL-SG3452P JetStream 52 portlu L2+ managed gigabit switchdir. 48×PoE+ portu ilə IP kamera, access point və VoIP telefonları birbaşa enerji ilə təmin edir. 384W PoE büdcəsi, 4×SFP uplink, VLAN, QoS və Omada SDN dəstəyi ilə korporativ və böyük şəbəkələr üçün ideal seçimdir.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)<https://eurotechnology.az/product/tp-link/tl-sg3452p>

Texniki göstəricilər

**48 Port**

Port sayı

**Managed**

Tip

**PoE+**

PoE

**1000mb/s**

Port sürəti

**400 W**

PoE gücü

Ətraflı məlumat

HARDWARE FEATURES	
Interface	• 48× 10/100/1000 Mbps RJ45 Ports • 4× Gigabit SFP Slots • 1× RJ45 Console Port • 1× Micro-USB Console Port
Fan Quantity	3
Power Supply	100-240 V AC~50/60 Hz
PoE+ Ports(RJ45)	• Standard: 802.3at/af compliant • PoE+ Ports: 48 Ports, up to 30 W per port • Power Budget: 384 W
Dimensions (W x D x H)	17.3 × 13.0 × 1.7 in (440 × 330 × 44 mm)
Mounting	Rack Mountable
Max Power Consumption	52.53 W (110 V/60 Hz) (no PD connected) 485.4 W (110 V/60 Hz) (with 384 W PD connected)
Max Heat Dissipation	179.13 BTU/hr (110 V/60 Hz) (no PD connected) 1656.19 BTU/hr (110 V/60 Hz) (with 384 W PD connected)
PERFORMANCE	
Switching Capacity	104 Gbps
Packet Forwarding Rate	77.4 Mpps
MAC Address Table	16 K
Jumbo Frame	9 KB
SOFTWARE FEATURES	

HARDWARE FEATURES	
Quality of Service	• 8 priority queues • 802.1p CoS/DSCP priority • Queue scheduling - SP (Strict Priority) - WRR (Weighted Round Robin) - SP+WRR • Bandwidth Control - Port/Flow based Rating Limiting • Smoother Performance • Action for Flows - Mirror (to supported interface) - Redirect (to supported interface) - Rate Limit - QoS Remark
L2 and L2+ Features	• Link Aggregation - Static link aggregation - 802.3ad LACP - Up to 8 aggregation groups and up to 8 ports per group • Spanning Tree Protocol - 802.1d STP - 802.1w RSTP - 802.1s MSTP - STP Security: TC Protect, BPDU Filter, BPDU Protect, Root Protect, Loop Protect • Loopback Detection - Port-based - VLAN based • Flow Control - 802.3x Flow Control - HOL Blocking Prevention • Mirroring - Port Mirroring - CPU Mirroring - One-to-One - Many-to-One - Tx/Rx/Both

HARDWARE FEATURES	
L2 Multicast	• Supports 511 (IPv4, IPv6) IGMP groups • IGMP Snooping - IGMP v1/v2/v3 Snooping - Fast Leave - IGMP Snooping Querier - IGMP Authentication • IGMP Authentication • MVR • MLD Snooping - MLD v1/v2 Snooping - Fast Leave - MLD Snooping Querier - Static Group Config - Limited IP Multicast • Multicast Filtering: 256 profiles and 16 entries per profile
VLAN	• VLAN Group - Max 4K VLAN Groups • 802.1q Tagged VLAN • MAC VLAN: 12 Entries • Protocol VLAN: Protocol Template 16, Protocol VLAN 16 • GVRP • VLAN VPN (QinQ) - Port-Based QinQ - Selective QinQ • Voice VLAN

HARDWARE FEATURES**Access Control List**

- Time-based ACL
- MAC ACL
 - Source MAC
 - Destination MAC
 - VLAN ID
 - User Priority
 - Ether Type
- IP ACL
 - Source IP
 - Destination IP
 - Fragment
 - IP Protocol
 - TCP Flag
 - TCP/UDP Port
 - DSCP/IP TOS
 - User Priority
- Combined ACL
- Packet Content ACL
- IPv6 ACL
- Policy
 - Mirroring
 - Redirect
 - Rate Limit
 - QoS Remark
- ACL apply to Port/VLAN

HARDWARE FEATURES
Security

- IP-MAC-Port Binding
- DHCP Snooping
- ARP Inspection
- IPv4 Source Guard
- IPv6-MAC-Port Binding
- DHCPv6 Snooping
- ND Detection
- IPv6 Source Guard
- DoS Defend
- Static/Dynamic Port Security
- Up to 64 MAC addresses per port
- Broadcast/Multicast/Unicast Storm Control
- kbps/ratio/pps control mode
- IP/Port/MAC based access control
- 802.1X
- Port based authentication
- Mac based authentication
- VLAN Assignment
- MAB
- Guest VLAN
- Support Radius authentication and accountability
- AAA (including TACACS+)
- Port Isolation
- Secure web management through HTTPS with SSLv3/TLS 1.2
- Secure Command Line Interface (CLI) management with SSHv1/SSHv2

HARDWARE FEATURES	
IPv6	• IPv6 Dual IPv4/IPv6 • Multicast Listener Discovery (MLD) Snooping • IPv6 ACL • IPv6 Interface • Static IPv6 Routing • IPv6 neighbor discovery (ND) • Path maximum transmission unit (MTU) discovery • Internet Control Message Protocol (ICMP) version 6 • TCPv6/UDPv6 • IPv6 applications - DHCPv6 Client - Ping6 - Tracert6 - Telnet (v6) - IPv6 SNMP - IPv6 SSH - IPv6 SSL - Http/Https - IPv6 TFTP
L3 Features	• 16 IPv4/IPv6 Interfaces • Static Routing - 48 static routes • Static ARP • 316 ARP Entries • Proxy ARP • Gratuitous ARP • DHCP Server • DHCP Relay • DHCP L2 Relay

HARDWARE FEATURES	
Management	• Web-based GUI • Command Line Interface (CLI) through console port, telnet • SNMPv1/v2c/v3 - Trap/Inform - RMON (1, 2, 3, 9 groups) • SDM Template • DHCP/BOOTP Client • 802.1ab LLDP/LLDP-MED • DHCP AutoInstall • Dual Image, Dual Configuration • CPU Monitoring • Cable Diagnostics • EEE • Password Recovery • SNTP • System Log
Advanced Features	• Support Omada Hardware Controller (OC200/OC300), Software Controller • Automatic Device Discovery • Batch Configuration • Batch Firmware Upgrading • Intelligent Network Monitoring • Abnormal Event Warnings • Unified Configuration • Reboot Schedule
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	• TL-SG3452P Switch • Power Cord • Quick Installation Guide • Rackmount Kit • Rubber Feet
Environment	• Operating Temperature: 0–40 °C (32–104 °F); • Storage Temperature: -40–70 °C (-40–158 °F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing