TP-LINK

TL-SL2218

Kod: 00-00003563 · Switchlər



TP-Link - TL-SL2218 (Smart 16-портовый 10/100 Мбит/с коммутатор + 2 гигабитных порта)

Texniki göstəricilər

16 Port
Port sayı

100mb/s
Port sürəti

Ətraflı məlumat

HARDWARE FEATURES	
Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1p
Interface	16 10/100Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX) 2 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX) 2 Combo Gigabit SFP Slots
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000Base-T: UTP category 5, 5e or above cable (maximum 100m) 1000BASE-X: MMF, SMF
Fan Quantity	Fanless
Power Supply	100~240VAC, 50/60Hz
Power Consumption	Maximum: 9.875W (220V/50Hz)
Dimensions (W x D x H)	17.3*7.1*1.7 in.(440*180*44 mm)
Mounting	Rack Mountable

PERFORMANCE	
Bandwidth/Backplane	7.2Gbps
MAC Address Table	8k
Packet Buffer Memory	5.4Mpps

SOFTWARE FEATURES	
Quality of Service	Support 802.1p CoS/DSCP priority Support 4 priority queues Queue scheduling: SP, WRR, SP+WRR Port/Flow-based Rate Limiting Voice VLAN

SOFTWARE FEATURES	
L2 Features	IGMP Snooping V1/V2/V3 802.3ad LACP (Up to 6 aggregation groups, containing 4 ports per group) Spanning Tree STP/RSTP/MSTP BPDU Filtering/Guard TC/Root Protect Loop back detection 802.3x Flow Control
VLAN	Supports up to 512 VLANs simultaneously (out of 4K VLAN IDs)
Access Control List	L2 L4 package filtering based on source and destination MAC address, IP address, TCP/UDP ports
Security	SSH v1/v2 SSL v2/v3/TLS v1 Port Security Broadcast/Multicast/Unknown-unicast Storm Control
Management	Web-based GUI and CLI management SNMP v1/v2c/v3,compatible with public MIBs and TP-LINK private MIBs RMON (1, 2, 3, 9 groups) CPU Monitoring Port Mirroring Firmware Upgrade: TFTP & Web System Diagnose: VCT SYSLOG & Public MIBS

OTHERS	
Certification	CE, FCC, RoHS
Package Contents	TL-SL2218; Power Cord; Installation Guide; Resource CD; Rackmount Kits; Rubber Feet
System Requirements	Microsoft® Windows® XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.

OTHERS	
Environment	Operating Temperature: 0℃~40℃ (32℉~104℉); Storage Temperature: -40℃~70℃ (-40℉~158℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az