UBIQUITI

U6-PRO

Kod: 00-00003064 · Access Pointlər



Ubiquiti Unifi 6 Pro, çoxlu sayda cihazları olan sistemlər üçün yüksək sürətli Wi-Fi 6 (802.11ax) texnologiyasına malik giriş nöqtəsidir . Unifi 6 Pro giriş nöqtəsinin ötürmə qabiliyyəti 5GHz 4x4-də 4.8 Gbits və 2.4GHz 2x2-də 570 Mbit-dən ibarət olmaqla 5.3 giqabiti keçir və 300-dən çox müştərini birləşdirməyə imkan verir.

Texniki göstəricilər

WiFi6 WIFI	**2.4Ghz/5Ghz** Tezlik
350+ Qoşulma sayı	**Mesh** Mesh
Dual band Genişlik	**PoE** PoE

Ətraflı məlumat

Size	Ø197 x 35 mm
Weight	Without fastening: 460 g With fastening: 600 g
Housing material	Plastic
Fastening material	Steel SGCC
Weatherproof	IP54
CPU	Dual-core Cortex® A53, 1 GHz
RAM	512 MB
Control Interface	Ethernet
Network interface	1 port 1 Gbit RJ45
Buttons	Reset to factory settings
LED colors	RGB
Nutrition	PoE+, Passive PoE (48B)
Power supply	UniFi PoE Switch 48V, 0.5A PoE power supply
Input voltage range	44 - 57B DC
Maximum power consumption	13W
Maximum transmit power	2.4 GHz - 22 dBm 5 GHz - 26 dBm
DESPITE	2.4 GHz - 2 x 2 5 GHz — 4 x4
Maximum data transfer rate	2.4 GHz - 573.5 Mbit 5 GHz - 4.8 Gbit
Antenna gain	2.4 GHz - 4 dBi 5 GHz - 6 dBi
Installation	On the ceiling or wall
Working temperature	-10 to 50° C
Operating humidity	from 5 to 95% without condensation

Certification	CE, FCC, IC
Wi-Fi standards	802.11a/b/g/Wi-Fi 4/Wi-Fi 5/Wi-Fi 6
Safety	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)
BSSID	8
VLAN	802.1Q
Advanced QoS	Yes
Guest Traffic Isolation	Yes
Number of clients	300+
Zero Wait DFS	Yes
Communication speed	
802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbit
802.11b	1, 2, 5.5, 11 Mbit
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbit
802.11n (Wi-Fi 4)	6.5 Mbit - 400 Mbit (MCS0 - MCS31, HT 20/40)
802.11ac (Wi-Fi 5)	6.5 Mbit - 3.4 Gbit (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80/160)
802.11ax (Wi-Fi 6)	7.3 Mbit - 4.8 Gbit (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80/160)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az