

# UAC-B122-AF28LM

HDTVI CAM UNV UAC-B122-AF28LM 2MP (2MP LightHunter , Microphone , Digital defog)

Model	UAC-B122-AF28LM
Brend	Uniview
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma	İR
İşıqlandırma məsafəsi	40 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8
Qoruma	IP67
Material	Plastik



## Specification

Model	UAC-B122-AF28LM
Sensor	
Pixel	2MP
Size	1/2.9"
Minimum illumination	0.005 lux (F1.6, AGC ON) 0 lux (IR on)
Lens	
Lens	2.8mm
Lens mount	M12
Angle of view	H: 101.5° V: 56.9° D: 117.4°
Illuminator	
Illuminator	Two IR illuminators
Illumination distance	40m
Lifetime	≥60,000 hours
Video	
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H)×720(V)

<b>Frame rate</b>	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC
<b>Shutter time</b>	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s
<b>Image</b>	
<b>Exposure mode</b>	Four modes: Global (default), BLC, HLC, DWDR
<b>Day/Night</b>	Three modes: Auto (default), Day, Night
<b>Digital noise reduction</b>	2D/3D
<b>White balance</b>	Two modes: Auto (default), Manual
<b>WDR</b>	DWDR
<b>Smart IR</b>	Support
<b>Flip</b>	Supports 180° horizontal flip, 180° vertical flip
<b>Defog</b>	Digital Defog
<b>Audio</b>	
<b>Microphone</b>	Built-in Mic
<b>Camera audio</b>	TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps
<b>Interface</b>	
<b>Power</b>	5.5mm power interface
<b>Video output</b>	BNC, supports TVI/AHD/CVI/CVBS
<b>Operating environment</b>	
<b>Temperature</b>	-30°C to 60°C (-22°F to 140°F)
<b>Humidity</b>	≤95% (RH, non-condensing)
<b>Surge protection</b>	4kV
<b>Ingress protection</b>	IP67
<b>General</b>	
<b>Power</b>	DC 12V (±25%), with reverse polarity protection, Max 3.2W
<b>Mount</b>	3D bracket supplied, surface mount (default), optional backbox, pole mount bracket
<b>Dimensions</b>	154mm*66mm*66mm (L*W*H)
<b>Material</b>	Metal+Plastic
<b>Weight</b>	240g (0.53lb)
<b>Certification</b>	CE, FCC, UL