

UAC-B122-AF28M-W

UAC-B122-AF28M-W 2MP ColorHunter 2.8MM IR 20M HD Built-in microp Fixed IR Mini Bullet TVI Kamera UNV

| | |
|-----------------------|------------------|
| Model | UAC-B122-AF28M-W |
| Brend | Uniview |
| İş mühiti | Outdoor |
| Növ | Analoq |
| Meqapixel | 2 MP |
| Mikrofon | Mic |
| İşıqlandırma | LED |
| İşıqlandırma məsafəsi | 40 m |
| Obyektiv | Sabit |
| Fokus | 2.8mm |
| Qoruma | IP67 |
| Material | Metal |



Specification

| | | |
|-------------------------|--|-----------------------------|
| Model | UAC-B122-AF28M-W | UAC-B122-AF40M-W |
| Sensor | | |
| Pixel | 2MP | |
| Size | 1/2.9" | |
| Minimum illumination | 0.005 lux (F1.6, AGC ON) 0 lux (white light on) | |
| Lens | | |
| Lens | 2.8mm | 4.0mm |
| Lens mount | M12 | |
| Angle of view | H: 101.5° V: 56.9° D: 117.4° | H: 83.8° V: 42.7° D: 100.1° |
| Illuminator | | |
| Illuminator | Two white-light illuminators | |
| Illumination distance | 40m | |
| Lifetime | ≥60,000 hours | |
| Video | | |
| Resolution | 1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V) | |
| Frame rate | TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC | |
| Shutter time | PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s | |
| Image | | |
| Exposure mode | Four modes: Global (default), BLC, HLC, DWDR | |
| Day/Night | 24/7 color images | |
| Digital noise reduction | 2D/3D | |
| White balance | Two modes: Auto (default), Manual | |
| WDR | DWDR | |

| | |
|-----------------------|---|
| Flip | Supports 180° horizontal flip, 180° vertical flip |
| Defog | Digital Defog |
| Audio | |
| Microphone | Built-in Mic |
| Camera audio | TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps |
| Interface | |
| Power | 5.5mm power interface |
| Video output | BNC, supports TVI/AHD/CVI/CVBS |
| Operating environment | |
| Temperature | -30°C to 60°C (-22°F to 140°F) |
| Humidity | ≤95% (RH, non-condensing) |
| Surge protection | 4kV |
| Ingress protection | IP67 |
| General | |
| Power | DC 12V (±25%), with reverse polarity protection, Max 3.12W |
| Mount | 3D bracket supplied, surface mount (default), optional junction box |
| Dimensions | 157.4mm*66.5mm*66.5mm (L*W*H) |
| Material | Metal |
| Weight | 279g (0.62lb) |
| Certification | CB, CE, FCC, UL |