

# UAC-B125-AF28M-W

UAC-B125-AF28M-W 5MP 2.8MM IR 40M ColourHunter Built-in micropho HD Fixed Mini Bullet TVI Kamera UNV



## Specifications

Model	UAC-B125-AF28M-W
Brand	Uniview
?? mühiti	Outdoor
Növ	Analoq
Meqapixel	5 MP
Mikrofon	Mic
???qland?rma	LED
???qland?rma m?saf?si	40 m
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Metal

## KEY FEATURES

	UAC-B125-AF28M-W	UAC-B125-AF40M-W
<b>Model</b>	UAC-B125-AF28M-W	UAC-B125-AF40M-W
<b>Sensor</b>		
<b>Pixel</b>	5MP	
<b>Size</b>	1/2.7"	
<b>Minimum illumination</b>	0.005 lux (F1.4, AGC ON) 0 lux (white light on)	
<b>Lens</b>		
<b>Lens</b>	2.8mm	4.0mm
<b>Lens mount</b>	M12	
<b>Angle of view</b>	H: 111.5° V: 58.9° D: 134.8°	H: 89.6° V: 48.3° D: 106.4°
<b>Illuminator</b>		
<b>Illuminator</b>	Two white-light illuminators	
<b>Illumination distance</b>	40m	
<b>Lifetime</b>	≥60,000 hours	
<b>Video</b>		
<b>Resolution</b>	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V) 4MP: 2560(H)×1440(V) 1080P: 1920(H)×1080(V)	
<b>Frame rate</b>	TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC	
<b>Shutter time</b>	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s	
<b>Image</b>		
<b>Exposure mode</b>	Four modes: Global (default), BLC, HLC, DWDR	
<b>Day/Night</b>	24/7 color images	
<b>Digital noise reduction</b>	2D	
<b>White balance</b>	Two modes: Auto (default), Manual	
<b>WDR</b>	DWDR	
<b>Flip</b>	Supports 180° horizontal flip, 180° vertical flip	
<b>Audio</b>		
<b>Microphone</b>	Built-in Mic	
<b>Camera audio</b>	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps	
<b>Interface</b>		
<b>Power</b>	5.5mm power interface	
<b>Video output</b>	BNC, supports TVI/AHD/CVI/CVBS	
<b>Operating environment</b>		
<b>Temperature</b>	-30°C to 60°C (-22°F to 140°F)	
<b>Humidity</b>	≤95% (RH, non-condensing)	
<b>Surge protection</b>	4kV	
<b>Ingress protection</b>	IP67	
<b>General</b>		

---

<b>Power</b>	<b>DC12V (<math>\pm 25\%</math>), with reverse polarity protection. Max 3.28W</b>
<b>Mount</b>	<b>3D bracket supplied, surface mount (default), optional junction box</b>
<b>Dimensions</b>	<b>157.4mm*66.5mm*66.5mm (L*W*H)</b>
<b>Material</b>	<b>Metal</b>
<b>Weight</b>	<b>279g (0.62lb)</b>
<b>Certification</b>	<b>CB, CE, FCC, UL</b>