

UAC-B134-ADF28MS-W

HDTVI CAM UNV UAC-B134-ADF28MS-W (4MP ColorHunter 2.8mm 40m , Microphone , Metal front face)

Model	UAC-B134-ADF28MS-W
Brend	Uniview
İş mühiti	Outdoor
Növ	Analoq
Meqapixel	4 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	40 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Metal



Specification

Model	UAC-B134-ADF28MS-W
Sensor	
Pixel	4MP
Size	1/1.8"
Minimum illumination	0.0005 lux (F1.0, AGC ON) 0 lux (white light on)
Lens	
Lens	2.8mm
Lens mount	M16
Angle of view	H: 105.9° V: 57.1° D: 125.0°
Illuminator	
Illuminator	Two white-light illuminators
Illumination distance	40m
Lifetime	≥60,000 hours
Video	
Resolution	4MP: 2560(H) × 1440(V) 1080P: 1920(H) × 1080(V)
Frame rate	CVI: 4MP@25fps (default), 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps TVI: 4MP@25fps, 4MP@15fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVBS: PAL, NTSC

Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s
Image	
Exposure mode	Four modes: Global (default), BLC, HLC, WDR
Day/Night	24/7 color images
Digital noise reduction	2D/3D
White balance	Two modes: Auto (default), Manual
WDR	120dB WDR
Flip	Supports 180° horizontal flip, 180° vertical flip
Defog	N/A
Audio	
Microphone	Built-in Mic
Camera audio	CVI: 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps
Interface	
Power	5.5mm power interface
Video output	BNC, supports TVI/AHD/CVI/CVBS
Operating environment	
Temperature	-30°C to 60°C (-22°F to 140°F)
Humidity	≤95% (RH, non-condensing)
Surge protection	4kV
General	
Power	DC 12V (±25%), with reverse polarity protection, Max 6.8W
Mount	3D bracket supplied, surface mount (default), optional junction box
Dimensions	206mm*73mm*73mm (L*W*H)
Material	Metal
Weight	463g (1.02lb)
Certification	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)
Safety	CE-LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU; (EU)2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)