

UAC-B134-ADF28MS-W

HDTVI CAM UNV UAC-B134-ADF28MS-W (4MP ColorHunter 2.8mm 40m , Microphone , Metal front face)

| | |
|-----------------------|--------------------|
| Model | UAC-B134-ADF28MS-W |
| Brend | Uniview |
| Növ | Analoq |
| Meqapixel | 4 MP |
| İşıqlandırma | LED |
| İşıqlandırma məsafəsi | 40 m |
| Mikrofon | Mic |
| Obyektiv | Sabit |
| Fokus | 2.8 |
| Qoruma | IP67 |
| Material | Metal |



Specification

| | |
|-----------------------|---|
| Model | UAC-B134-ADF28MS-W |
| Sensor | |
| Pixel | 4MP |
| Size | 1/1.8" |
| Minimum illumination | 0.0005 lux (F1.0, AGC ON) 0 lux (white light on) |
| Lens | |
| Lens | 2.8mm |
| Lens mount | M16 |
| Angle of view | H: 105.9° V: 57.1° D: 125.0° |
| Illuminator | |
| Illuminator | Two white-light illuminators |
| Illumination distance | 40m |
| Lifetime | ≥60,000 hours |
| Video | |
| Resolution | 4MP: 2560(H) × 1440(V) 1080P: 1920(H) × 1080(V) |
| Frame rate | CVI: 4MP@25fps (default), 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps TVI: 4MP@25fps, 4MP@15fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVBS: PAL, NTSC |

| | |
|-------------------------|--|
| Shutter time | PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s |
| Image | |
| Exposure mode | Four modes: Global (default), BLC, HLC, WDR |
| Day/Night | 24/7 color images |
| Digital noise reduction | 2D/3D |
| White balance | Two modes: Auto (default), Manual |
| WDR | 120dB WDR |
| Flip | Supports 180° horizontal flip, 180° vertical flip |
| Defog | N/A |
| Audio | |
| Microphone | Built-in Mic |
| Camera audio | CVI: 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps |
| Interface | |
| Power | 5.5mm power interface |
| Video output | BNC, supports TVI/AHD/CVI/CVBS |
| Operating environment | |
| Temperature | -30°C to 60°C (-22°F to 140°F) |
| Humidity | ≤95% (RH, non-condensing) |
| Surge protection | 4kV |
| General | |
| Power | DC 12V (±25%), with reverse polarity protection, Max 6.8W |
| Mount | 3D bracket supplied, surface mount (default), optional junction box |
| Dimensions | 206mm*73mm*73mm (L*W*H) |
| Material | Metal |
| Weight | 463g (1.02lb) |
| Certification | |
| EMC | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B) |
| Safety | CE-LVD (EN 62368-1) |
| Environment | CE-RoHS (2011/65/EU; (EU)2015/863); WEEE (2012/19/EU) |
| Protection | IP67 (IEC 60529) |