UNIVIEW

UAC-B315-ADZLM

Kod: 00-00006072 · Kamera



UNV UAC-B315-ADZLM (5MP) – LightHunter texnologiyalı və motorizə olunmuş varifokal (zoom) obyektivli analoq bullet kameradır. Daxili mikrofonu (koaksial kabel üzərindən səs), 40 metrədək IR gecə görüntüsü və IP67 toz-su keçirməyən metal korpusu ilə hər hava şəraitində güclü təhlükəsizlik yaradır.

Texniki göstəricilər

Analoq Növ	**5 MP** Meqapixel
Motorized Obyektiv	**2.8 - 12mm** Fokus
İR İşıqlandırma	**50 m** İşıqlandırma məsafəsi
Mic Mikrofon	**IP67** Qoruma
Plastik Material	**Outdoor** İş mühiti

Ətraflı məlumat

Camera	
Max Resolution	5 MP
Sensor Size	1/2.7" CMOS
Min. Illumination	0.005 lux (F1.6, AGC ON) 0 lux (IR on)
Lens	
Focus	2.8 to 12 mm
Lens Mount	Φ14
Angle of View (H)	107.8° ~ 36.5°
Angle of View (V)	58.5° ~ 20.5°
Angle of View (D)	127.0° ~ 41.3°
Illuminator	
Illuminator Number	Three IR illuminators
Illumination Distance	50m
Lifetime	≥ 60000 hours
Video	
Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 4MP: 2560(H)×1440(V) 1080P: 1920(H)×1080(V)
Frame Rate	CVI: 5MP@25fps (default), 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps TVI: 5MP@20fps 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25 s-1/50000 s, NTSC: 1/30 s-1/50000 s
Image	
Exposure Mode	Four modes: Global (default), BLC, HLC, WDR
Day/Night	Three modes: Auto (default), Day, Night

Digital Noise Reduction	2D/3D
White Balance	Two modes: Auto (default), Manual
WDR	120 dB WDR
Smart IR	Support
Flip	Supports 180°horizontal flip, 180°vertical flip
Digital Defog	N/A
Audio	
Built-in Mic	Support
Camera Audio	CVI: 5MP@25fps,5MP@20fps, 4MP@25fps, 4MP@30fps
Interface	
Power Interface	5.5 mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
Operating Environment	
Temperature	-30 ℃ to 60 ℃ (-22 ℉ to 140 ℉)
Humidity	≤ 95% RH (non-condensing)
Surge Protection	4 KV for power, 4 KV for video output interfaces
General	
Power	DC 12 V±25%
Power Consumption	MAX 4.7W
Mount	Corner Mount, Pole Mount
Dimensions	198mm*74mm*74mm (L*W*H)
Material	Metal + Plastic
Weight	332g(0.73lb)
OSD Menu Language	11 Languages: English, German, Spanish (Latin America), French, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Turkish
Certification	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035), FCC (FCC 47 CFR part15 B)

Safety	CE-LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU; (EU) 2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az