

UAC-B315-ADZLM

UNV UAC-B315-ADZLM (5MP) – LightHunter texnologiyalı və motorizə olunmuş varifokal (zoom) obyektivli analoq bullet kameradır. Daxili mikrofonu (koaksial kabel üzərindən səs), 40 metrədək IR gecə görüntüsü və IP67 toz-su keçirməyən metal korpusu ilə hər hava şəraitində güclü təhlükəsizlik yaradır.



Specifications

Model	UAC-B315-ADZLM
Brand	Uniview
Növ	Analoq
Meqapixel	5 MP
Obyektiv	Motorized
Fokus	2.8 - 12mm
İrəli görüşmə məsafəsi	IR
İrəli görüşmə məsafəsi	50 m
Mikrofon	Mic
Qoruma	IP67
Material	Plastik
İstifadə mühiti	Outdoor

KEY FEATURES

Camera

Max Resolution	5 MP
Sensor Size	1/2.7" CMOS
Min. Illumination	0.005 lux (F1.6, AGC ON) 0 lux (IR on)

Lens

Focus	2.8 to 12 mm
Lens Mount	Φ14
Angle of View (H)	107.8° ~ 36.5°
Angle of View (V)	58.5° ~ 20.5°
Angle of View (D)	127.0° ~ 41.3°

Illuminator

Illuminator Number	Three IR illuminators
Illumination Distance	50m

Lifetime	≥ 60000 hours
----------	---------------

Video

Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 4MP: 2560(H)×1440(V) 1080P: 1920(H)×1080(V)
Frame Rate	CVI: 5MP@25fps (default), 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps TVI: 5MP@20fps 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25 s-1/50000 s, NTSC: 1/30 s-1/50000 s

Image

Exposure Mode	Four modes: Global (default), BLC, HLC, WDR
Day/Night	Three modes: Auto (default), Day, Night
Digital Noise Reduction	2D/3D

White Balance	Two modes: Auto (default), Manual
WDR	120 dB WDR

Smart IR	Support
Flip	Supports 180°horizontal flip, 180°vertical flip
Digital Defog	N/A

Audio

Built-in Mic	Support
Camera Audio	CVI: 5MP@25fps,5MP@20fps, 4MP@25fps, 4MP@30fps

Interface

Power Interface	5.5 mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS

Operating Environment

Temperature	-30 ℃ to 60 ℃ (-22 ℃ to 140 ℃)
Humidity	≤ 95% RH (non-condensing)
Surge Protection	4 KV for power, 4 KV for video output interfaces

General	
Power	DC 12 V±25%
Power Consumption	MAX 4.7W
Mount	Corner Mount, Pole Mount
Dimensions	198mm*74mm*74mm (L*W*H)
Material	Metal + Plastic
Weight	332g(0.73lb)
OSD Menu Language	11 Languages: English, German, Spanish (Latin America), French, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Turkish
Certification	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035), FCC (FCC 47 CFR part15 B)
Safety	CE-LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU; (EU) 2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)