

UAC-P112-AF40-W

HDTVI CAM UNV UAC-P112-AF40-W 2MP PTZ



Model	UAC-P112-AF40-W
Brend	Uniview
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	30 m
Mikrofon	Mic
Obyektiv	PTZ
Fokus	4
Qoruma	IP66
Material	Plastik

Specification

Model	UAC-P112-AF40-W
Sensor	
Pixel	2MP
Size	1/2.9"
Minimum illumination	0.005 lux (F1.6, AGC ON) 0 lux (white light on)
Lens	
Lens	4.0mm
Lens mount	M12
Angle of view	H: 83.8° V: 42.7° D: 100.1°
Illuminator	
Illuminator	Eight white-light illuminators
Illumination distance	30m
Lifetime	≥20,000 hours
Video	
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@30fps, 720P@25fps CVBS: PAL, NTSC
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s
Image	
Exposure mode	Four modes: Global (default), BLC, HLC, DWDR

Day/Night	24/7 color images
Digital noise reduction	2D/3D
White balance	Two modes: Auto (default), Manual
WDR	DWDR
Flip	Supports 180° horizontal flip, 180° vertical flip
Defog	Digital Defog
Pan & Tilt	
Pan range/speed	Pan range: 0° to 345° Pan speed: 1° to 40°/s
Tilt range/speed	Tilt range: 0° to 90° Tilt speed: 1° to 30°/s
Presets	32
Control mode	Coaxial control, RS485 control
Audio	
Microphone	Built-in Mic
Camera audio	TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps
Interface	
Power	5.5mm power interface
Video output	BNC, supports TVI/AHD/CVI/CVBS
RS485	1* RS485, supports 9600bps, 4800bps, 2400bps, 1200bps
Operating environment	
Temperature	-30°C to 60°C (-22°F to 140°F)
Humidity	≤95% (RH, non-condensing)
Surge protection	4kV for power and video output interfaces, 6kV for RS485 interface
Ingress protection	IP66
General	
Power	DC 12V (±25%), with reverse polarity protection. Max 8.5W
Mount	Supplied bracket for wall or pendent mount; optional bracket and junction box (sold separately) for pole mount and corner mount
Dimensions	Φ118mm*190mm (diameter*height)
Material	Plastic
Weight	477g (1.05lb)
Certification	CB, CE, FCC