eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

UNIVIEW

UAC-P112-AF40-W

Kod: 00-00004636 · Kamera



HDTVI CAM UNV UAC-P112-AF40-W 2MP PTZ

Texniki göstəricilər

Analoq Növ	**2 MP** Meqapixel
LED İşıqlandırma	**30 m** İşıqlandırma məsafəsi
Mic Mikrofon	**PTZ** Obyektiv
4mm Fokus	**IP66** Qoruma
Plastik Material	**Outdoor** İş mühiti

Ətraflı məlumat

Model	**UAC-P112-AF40-W**
Sensor	
Pixel	2MP
Size	1/2.9"
Minimum illumination	0.005 lux (F1.6, AGC ON) 0 lux (white light on)
Lens	
Lens	4.0mm
Lens mount	M12
Angle of view	H: 83.8° V: 42.7° D: 100.1°
Illuminator	
Illuminator	Eight white-light illuminators
Illumination distance	30m
Lifetime	≥20,000 hours
Video	
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@30fps, 720P@25fps CVBS: PAL, NTSC
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s–1/50000s
Image	
Exposure mode	Four modes: Global (default), BLC, HLC, DWDR
Day/Night	24/7 color images
Digital noise reduction	2D/3D
White balance	Two modes: Auto (default), Manual

WDR	DWDR
Flip	Supports 180° horizontal flip, 180° vertical flip
Defog	Digital Defog
Pan & Tilt	
Pan range/speed	Pan range: 0° to 345° Pan speed: 1° to 40°/s
Tilt range/speed	Tilt range: 0° to 90° Tilt speed: 1° to 30°/s
Presets	32
Control mode	Coaxial control, RS485 control
Audio	
Microphone	Built-in Mic
Camera audio	TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps
Interface	
Power	5.5mm power interface
Video output	BNC, supports TVI/AHD/CVI/CVBS
RS485	1* RS485, supports 9600bps, 4800bps, 2400bps, 1200bps
Operating environment	
Temperature	-30°C to 60°C (-22°F to 140°F)
Humidity	≤95% (RH, non-condensing)
Surge protection	4kV for power and video output interfaces, 6kV for RS485 interface
Ingress protection	IP66
General	
Power	DC 12V (±25%), with reverse polarity protection. Max 8.5W
Mount	Supplied bracket for wall or pendent mount; optional bracket and junction box (sold separately) for pole mount and corner mount
Dimensions	Φ118mm*190mm (diameter*height)
Material	Plastic

Weight	477g (1.05lb)
Certification	CB, CE, FCC

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az