UNIVIEW

UAC-T112-AF28-DL

Kod: 00-00006068 · Kamera



Uniview UAC-T112-AF28-DL – 2MP (Full HD) təsvir ölçülü və Dual Light (qoşa işıqlandırma) texnologiyalı analoq Turret kamera. Quraşdırılmış mikrofon (daxili səs), 2.8mm fiks obyektiv, gecə rəngli görüntü və IP67 küçə mühafizəsi ilə obyektləriniz üçün etibarlı təhlükəsizlik həllidir.

Texniki göstəricilər

Analoq Növ	**2 MP** Meqapixel
LED İşıqlandırma	**20 m** İşıqlandırma məsafəsi
Sabit Obyektiv	**2.8mm** Fokus
Mic Mikrofon	**IP67** Qoruma
Plastik Material	**Indoor** İş mühiti

Ətraflı məlumat

Camera	
Max Resolution	2 MP
Sensor Size	1/3.0" CMOS
Min. Illumination	0.01 lux (F2.0, AGC ON) 0 lux (Illuminator ON)
Lens	
Focus	2.8 mm
Lens Mount	M12
Angle of View (H)	91.5°
Angle of View (V)	51.2°
Angle of View (D)	106.3°
Illuminator	
Illuminator Number	Two IR illuminators; One white-light illuminator
Illumination Distance	IR: 20m (65.6 ft) White light: 20m (65.6 ft)
Lifetime	≥ 60000 hours
Video	
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame Rate	TVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps AHD: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps CVI: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25 s-1/50000 s, NTSC: 1/30 s-1/50000 s
Image	
Exposure Mode	Four modes: Global (default), BLC, HLC, DWDR
Day/Night	Three modes: Auto (default), Day, Night

Digital Noise Reduction	2D/3D
White Balance	Two modes: Auto (default), Manual
WDR	DWDR
Light Mode	Dual light (default) , Infrared, White light
Flip	Supports 180°horizontal flip, 180°vertical flip
Digital Defog	N/A
Audio	
Built-in Mic	Support
Camera Audio	TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps
Interface	
Power Interface	5.5 mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
Operating Environment	
Temperature	-30 ℃ to 60 ℃ (-22 ℉ to 140 ℉)
Humidity	≤ 95% RH (non-condensing)
Surge Protection	4 KV for power, 4 KV for video output interfaces
General	
Power	DC 12 V ± 25%
Power Consumption	MAX 2.8W
Mount	Wall Mount, Pole Mount, Corner Mount, Pendant Mount
Dimensions	Φ118mm*96mm (diameter*height)
Material	Plastic
Weight	184g (0.41lb)
OSD Menu Language	11 Languages: English, German, Spanish (Latin America), French, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Turkish
Certification	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035), FCC (FCC 47 CFR part15 B)

Safety	CE-LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU; (EU) 2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az