

# UAC-T112-F28

UAC-T112-F28 2MP 2.8MM IR 20M HD Fixed IR Turret TVI Kamera UNV



## Specifications

Model	UAC-T112-F28
Brand	Uniview
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
??qland?rma m?saf?si	20 m
Obyektiv	Sabit
Fokus	2.8mm
??qland?rma	IR
Material	Plastik
?? mühiti	Indoor

## KEY FEATURES

Model	UAC-T112-F28
Sensor	
Pixel	2MP
Size	1/3"
Minimum illumination	0.02 lux (F2.0, AGC ON) 0 lux (IR on)
Lens	
Lens	2.8mm
Lens mount	M12
Angle of view	H: 90.5° V: 49.6° D: 109.5°
Illuminator	
Illuminator	One IR illuminator
Illumination distance	20m
Lifetime	≥60,000 hours
Image	
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H)×720(V)
Frame rate	TVI/AHD/CVI: 1080P@30fps, 1080P@25fps; 720P@30fps, 720P@25fps CVBS: PAL, NTSC
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s
Image	
Exposure mode	4 modes: Global (default), BLC, HLC, DWDR
Day/Night	3 modes: Auto (default), Day, Night
Digital noise reduction	2D
White balance	Two modes: Auto (default), Manual
WDR	DWDR
Smart IR	Support
Flip	Supports 180° horizontal flip, 180° vertical flip.
Interface	
Power	5.5mm power interface
Video output	BNC, supports TVI/AHD/CVI/CVBS
Operating environment	
Temperature	-30ℳ to 60ℳ (-22ℳ to 140ℳ)
Humidity	≤95% (RH, non-condensing)
Surge protection	4KV
Ingress protection	IP67
General	
Power	DC 12V(±25%), with reverse polarity protection and surge protection, Max 2.88W
Mount	Surface mount (default), optional backbox, wall mount bracket
Dimensions	Φ118mm*96mm (diameter*height)
Material	Plastic
Weight	182g (0.401lb)

---

Certification

CB, CE, FCC