

# UAC-T122-AF28LM

HDTVI CAM UNV UAC-T122-AF28LM (2MP LightHunter Microphone Digital defog)



|                       |                 |
|-----------------------|-----------------|
| Model                 | UAC-T122-AF28LM |
| Brend                 | Uniview         |
| Növ                   | Analoq          |
| Meqapixel             | 2 MP            |
| Mikrofon              | Mic             |
| İşıqlandırma          | İR              |
| İşıqlandırma məsafəsi | 40 m            |
| Obyektiv              | Sabit           |
| Fokus                 | 2.8             |
| Qoruma                | IP67            |
| Material              | Plastik         |

## Specification

|                       |  |
|-----------------------|--|
| Model                 | UAC-T122-AF28LM  |
| Sensor                |  |
| Pixel                 | 2MP  |
| Size                  | 1/2.9"   |
| Minimum illumination  | 0.005 lux (F1.6, AGC ON)<br>0 lux (IR on)  |
| Lens                  |  |
| Lens                  | 2.8mm  |
| Lens mount            | M12  |
| Angle of view         | H: 101.5° V: 56.9° D: 117.4°   |
| Illuminator           |  |
| Illuminator           | Two IR illuminators  |
| Illumination distance | 40m  |
| Lifetime              | ≥60,000 hours  |
| Video                 |  |
| Resolution            | 1080P: 1920(H)×1080(V)<br>720P: 1280(H) ×720(V)  |
| Frame rate            | TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps<br>CVBS: PAL, NTSC |

|                         |  |
|-------------------------|--|
| Shutter time            | PAL: 1/25s-1/50000s<br>NTSC: 1/30s-1/50000s                    |
| Image                   |  |
| Exposure mode           | Four modes: Global (default), BLC, HLC, DWDR                   |
| Day/Night               | Three modes: Auto (default), Day, Night                        |
| Digital noise reduction | 2D/3D  |
| White balance           | Two modes: Auto (default), Manual                              |
| WDR                     | DWDR   |
| Smart IR                | Support  |
| Flip                    | Supports 180° horizontal flip, 180° vertical flip              |
| Defog                   | Digital Defog  |
| Audio                   |  |
| Microphone              | Built-in Mic   |
| Camera audio            | TVI: 1080P@25fps, 1080P@30fps<br>CVI: 1080P@25fps, 1080P@30fps |
| Interface               |  |
| Power                   | 5.5mm power interface  |
| Video output            | BNC, supports TVI/AHD/CVI/CVBS                                 |
| Operating environment   |  |
| Temperature             | -30°C to 60°C (-22°F to 140°F)                                 |
| Humidity                | ≤95% (RH, non-condensing)                                      |
| Surge protection        | 4kV  |
| Ingress protection      | IP67   |
| General                 |  |
| Power                   | DC 12V (±25%), with reverse polarity protection, Max 3.2W      |
| Mount                   | Surface mount (default), optional backbox, wall mount bracket  |
| Dimensions              | Φ111mm*98mm (diameter*height)                                  |
| Material                | Metal+Plastic  |
| Weight                  | 334g (0.74lb)  |
| Certification           | CE, FCC, UL  |