

# UAC-T122-AF28M-W

UAC-T122-AF28M-W 2MP ColorHunter 2.8MM IR 40M HD Fixed IR Built-in microphone Turret TVI Kamera UNV



## Specifications

Model	UAC-T122-AF28M-W
Brand	Uniview
?? mühiti	Indoor
Növ	Analoq
Meqapixel	2 MP
Mikrofon	Mic
???qland?rma	LED
???qland?rma m?saf?si	40 m
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Metal

## KEY FEATURES

Model	UAC-T122-AF28M-W	UAC-T122-AF40M-W
Sensor		
Pixel	2MP	
Size	1/2.9"	
Minimum illumination	0.005lux (F1.6, AGC ON) 0 lux (white light on)	
Lens		
Lens	2.8mm	4.0mm
Lens mount	M12	
Angle of view	H: 101.5° V: 56.9° D: 117.4°	H: 83.8° V: 42.7° D: 100.1°
Illuminator		
Illuminator	Two white-light illuminators	
Illumination distance	40m	
Lifetime	≥60,000 hours	
Video		
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)	
Frame rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC	
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s	
Image		
Exposure mode	Four modes: Global (default), BLC, HLC, DWDR	
Day/Night	24/7 color images	
Digital noise reduction	2D/3D	
White balance	Two modes: Auto (default), Manual	
WDR	DWDR	
Flip	Supports 180° horizontal flip, 180° vertical flip	
Defog	Digital Defog	
Audio		
Microphone	Built-in Mic	
Camera audio	TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps	
Interface		
Power	5.5mm power interface	
Video output	BNC, supports TVI/AHD/CVI/CVBS	
Operating environment		
Temperature	-30°C to 60°C (-22°F to 140°F)	
Humidity	≤95% (RH, non-condensing)	
Surge protection	4kV	
Ingress protection	IP67	
General		
Power	DC 12V (±25%), with reverse polarity protection. Max 3.12W	
Mount	Surface mount (default), optional junction box and wall mount bracket	

---

<b>Dimensions</b>	<b>Φ111mm*96mm (diameter*height)</b>
<b>Material</b>	<b>Metal and plastic</b>
<b>Weight</b>	<b>356g (0.79lb)</b>
<b>Certification</b>	<b>CB, CE, FCC, UL</b>