

## UAC-T142-ACF28LM-DL

Uniview UAC-T142-ACF28LM-DL 2MP ColorHunter Light Hunter smart dual-light turret analog kamera - 2.8mm geniş bucaqlı obyektiv, IP67 qoruma, 40m IR/ağ işıq məsafəsi, ikitərəfli səs, aktiv səs/işıq xəbərdarlığı və 4-ü-1 çıxış (TVI/AHD/CVI/CVBS) dəstəyi ilə çöldə quraşdırma üçün ideal təhlükəsizlik kamerasıdır



### Specifications

Model	UAC-T142-ACF28LM-DL
Brand	Uniview
Növ	Analoq
Meqapixel	2 MP
Obyektiv	Sabit
Fokus	2.8mm
Yaxınlıq	LED
Yaxınlıq məsafəsi	40 m
Mikrofon	Mic
Qoruma	IP67
Material	Metal
Çalışma mühiti	Outdoor

## KEY FEATURES

Category	Specification
Type	4-in-1 Analog Turret Camera
Series	Whale Series / Light Hunter Series
Megapixel	2 MP (1920×1080)
Image Sensor	1/3.0" Progressive Scan CMOS
Lens	2.8 mm fixed
Focal Length	2.8 mm
Min. Illumination	0.003 lux (color), 0 lux (illuminator ON)
Field of View (H)	96.5°
Field of View (V)	54.5°
Field of View (D)	109.5°
Illumination Type	1 IR LED + 1 White Light LED (Smart Dual-Light)
Illumination Distance	IR: 40 m / White Light: 40 m
Built-in Microphone	Yes
Built-in Speaker	Yes
Two-way Audio	Yes (TVI 1080P only)
Active Deterrence	Yes (visual + auditory warnings, TVI 1080P only)
Video Output	BNC (TVI/AHD/CVI/CVBS)
WDR	DWDR
Noise Reduction	2D/3D DNR
Day/Night	Auto (ICR), Day, Night
Ingress Protection	IP67
Material	Metal + Plastic
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Operating Humidity	≤ 95% RH (non-condensing)
Power Supply	DC 12V ± 25%
Power Consumption	MAX 3.4W
Surge Protection	4 kV (power), 4 kV (video)
Dimensions (D×H)	Φ117.8 × 96.5 mm
Weight	256 g (0.57 lb)
Mounting	Corner mount, pole mount, wall mount, pendant mount
Storage	None (connects to DVR/XVR)
Operating Environment	Outdoor compatible