eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

UNIVIEW

UAC-T312-AZM

Kod: 00-00005971 · Kamera



Uniview UAC-T312-AZM, koaksial kabel üzərindən yüksək keyfiyyətli video və səs ötürə bilən 2 Meqapikselli (1080p Full HD) Turret (Qübbə) tipli analoq kameradır. Cihazın ən böyük üstünlüklərindən biri üzərindəki 2.7-13.5 mm Motorizə Varifokal (VF) obyektivdir. Bu obyektiv sayəsində kameranın baxış bucağını (yaxınlaşdırma və netləşdirməni) nərdivana çıxmadan, birbaşa qeydiyyat cihazı (DVR) və ya mobil tətbiq üzərindən avtomatik idarə etmək mümkündür. Uniview-in xüsusi LightHunter texnologiyası ilə təchiz edildiyi üçün, standart kameraların ağ-qara rejimə keçdiyi zəif işıqlı mühitlərdə belə aydın və rəngli çəkilişə davam edir. Zülmət qaranlıqda isə 40 metrə qədər təsirli olan ağıllı İnfraqırmızı (Smart IR) işıqlandırması dövrəyə girir. Daxili mikrofonu AoC (Audio over Coaxial) texnologiyasını dəstəkləyir, yəni əlavə səs kabeli çəkmədən mövcud görüntü şnuru ilə səsi DVR-a ötürür.

Texniki göstəricilər

Analoq Növ	**2 MP** Meqapixel
Varifokal Obyektiv	**2.7 - 13.5mm** Fokus
İR İşıqlandırma	**40 m** İşıqlandırma məsafəsi
Mic Mikrofon	**IP67** Qoruma
Metal Material	**Indoor** İş mühiti

Ətraflı məlumat

	UAC-T312-AZM
Camera	
Max Resolution	2 MP
Sensor Size	1/3.0" CMOS
Min. Illumination	0.005 lux (F1.6, AGC ON) 0 lux (IR on)
Lens	
Focus	2.8 to 12 mm
Lens Mount	Φ14
Angle of View (H)	91.3° ~ 31.3°
Angle of View (V)	52.2° ~ 18.5°
Angle of View (D)	106.8° ~ 35.9°
Illuminator	
Illuminator Number	Two IR illuminators
Illumination Distance	40 m
Lifetime	≥ 60000 hours
Video	
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame Rate	CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps TVI: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps AHD: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25 s-1/50000 s, NTSC: 1/30 s-1/50000 s
Image	
Exposure Mode	Four modes: Global (default), BLC, HLC, DWDR
Day/Night	Three modes: Auto (default), Day, Night

Digital Noise Reduction	2D/3D
White Balance	Two modes: Auto (default), Manual
WDR	DWDR
Smart IR	Support
Flip	Supports 180°horizontal flip, 180°vertical flip
Digital Defog	N/A
Audio	
Built-in Mic	Support
Camera Audio	CVI: 1080P@25fps, 1080P@30fps * Audio function of the camera is only available when the camera is used with our G3/Q3/U3 series XVRs.
Interface	
Power Interface	5.5 mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
Operating Environment	
Temperature	-30 ℃ to 60 ℃ (-22 ℉ to 140 ℉)
Humidity	≤ 95% RH (non-condensing)
Surge Protection	4 KV for power, 4 KV for video output interfaces
General	
Power	DC 12 V±25%
Power Consumption	MAX 2.78W
Mount	Wall Mount, Pole Mount, Corner Mount, Pendant Mount
Dimensions	Φ129 x 110mm (Ø5.1” x 4.3”)
Material	Metal
Weight	609g(1.34lb)
OSD Menu Language	11 Languages: English, German, Spanish (Latin America), French, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Turkish
Certification	

EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035), FCC (FCC 47 CFR part15 B)
Safety	CE-LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU; (EU) 2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az