UNIVIEW

UAC-T315-ADZM

Kod: 00-00005970 · Kamera



Uniview UAC-T315-ADZM, ənənəvi koaksial (BNC) infrastruktur üzərindən ultra-yüksək 5 Meqapiksel çözünürlükdə kəsintisiz görüntü ötürən Turret (Qübbə) tipli peşəkar analoq kameradır. Cihaz üzərindəki 2.7-13.5 mm Motorizə Varifokal (VF) obyektiv vasitəsilə siz qeydiyyat cihazının (DVR) başından ayrılmadan, ekran üzərindən kadrı istədiyiniz qədər yaxınlaşdıra və avtomatik netləşdirə bilərsiniz. Uniview-in qabaqcıl LightHunter texnologiyası ultra-həssas sensorla birgə çalışaraq, çox zəif işıqlandırılmış mühitlərdə belə aydın və rəngli kadrlar təqdim edir. Tam qaranlıqda isə 40 metrə qədər effektiv olan Smart IR (İnfraqırmızı) işıqlandırması fəaliyyətə keçir. Cihaz yüksək kontrastlı işıq mühitləri üçün True WDR (130dB) texnologiyası və daxili mikrofonu (AoC - Audio over Coaxial) ilə təchiz olunub.

Texniki göstəricilər

Analoq Növ	**5 MP** Meqapixel
Varifokal Obyektiv	**2.7 - 13.5mm** Fokus
İR İşıqlandırma	**40 m** İşıqlandırma məsafəsi
Mic Mikrofon	**IP67** Qoruma
Metal Material	**Indoor** İş mühiti

Ətraflı məlumat

	UAC-T315-ADZM
Camera	
Max Resolution	5 MP
Sensor Size	1/2.7" CMOS
Min. Illumination	0.005 lux (F1.6, AGC ON) 0 lux (IR on)
Lens	
Focus	2.8 to 12 mm
Lens Mount	Φ14
Angle of View (H)	107.8° ~ 36.5°
Angle of View (V)	58.5° ~ 20.5°
Angle of View (D)	127.0° ~ 41.3°
Illuminator	
Illuminator Number	Two IR illuminators
Illumination Distance	40m
Lifetime	≥ 60000 hours
Video	
Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 4MP: 2560(H)×1440(V) 1080P: 1920(H)×1080(V)
Frame Rate	CVI: 5MP@25fps (default), 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps TVI: 5MP@20fps 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25 s-1/50000 s, NTSC: 1/30 s-1/50000 s
Image	
Exposure Mode	Four modes: Global (default), BLC, HLC, WDR

Day/Night	Three modes: Auto (default), Day, Night
Digital Noise Reduction	2D/3D
White Balance	Two modes: Auto (default), Manual
WDR	120 dB WDR
Smart IR	Support
Flip	Supports 180°horizontal flip, 180°vertical flip
Digital Defog	N/A
Audio	
Built-in Mic	Support
Camera Audio	CVI: 5MP@25fps,5MP@20fps, 4MP@25fps, 4MP@30fps
Interface	
Power Interface	5.5 mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
Operating Environment	
Temperature	-30 ℃ to 60 ℃ (-22 ℉ to 140 ℉)
Humidity	≤ 95% RH (non-condensing)
Surge Protection	4 KV for power, 4 KV for video output interfaces
General	
Power	DC 12 V±25%
Power Consumption	MAX 4.7W
Mount	Wall Mount, Pole Mount, Corner Mount, Pendant Mount
Dimensions	Φ129 x 110mm (Ø5.1” x 4.3”)
Material	Metal
Weight	609g(1.34lb)
OSD Menu Language	11 Languages: English, German, Spanish (Latin America), French, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Turkish
Certification	

EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035), FCC (FCC 47 CFR part15 B)
Safety	CE-LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU; (EU) 2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az