

# UAP-AC-M

Ubiquiti UniFi AC Mesh həm binalarda, həm də açıq yerlərdə 360 dərəcə yüksək sürətli WiFi şəbəkələrini yerləşdirmək üçün nəzərdə tutulmuş universal bütün hava şəraitinə uyğun giriş nöqtəsidir.



|              |             |
|--------------|-------------|
| Model        | UAP-AC-M    |
| Brend        | Ubiquiti    |
| WIFI         | WiFi5       |
| Tezlik       | 2.4Ghz/5Ghz |
| Qoşulma sayı | 250+        |
| Mesh         | Mesh        |
| Genişlik     | Dual band   |
| PoE          | PoE         |

## Specification

|                             |  |
|-----------------------------|--|
| Dimensions                  | 353 x 46 x 34.4 mm   |
| Weight                      | 152 g  |
| Speed ??in the 2.4 GHz band | 300 Mbps   |
| Speed ??at 5 GHz            | 867 Mbps   |
| Usage                       | External/internal  |
| Network interface           | 1x 10/100/1000 Ethernet port   |
| Buttons                     | Reset  |
| Nutrition method            | Passive PoE (power over twisted pair) 24 V (Pins: 4, 5 (+) and 7, 8 (-)) Supports 803.2af standard, Method A (Pins: 1, 2 (+) and 3, 6 (-))(Supported voltage range: 44 - 57 VDC) |
| Power unit                  | Gigabit PoE 24 V, 0.5 A (Only one UniFi AC Mesh unit includes a PoE power supply)  |
| Energy saving               | Supported  |
| PoE (output)                | 48V Pass-Through (Pins: 1, 2 (+) and 3, 6 (-))   |
| Maximum power consumption   | 8.5 W  |
| Maximum radio output power  | 2.4 GHz: 20 dBm<br>5 GHz: 20 dBm   |
| Antenna                     | 2x External dual band omnidirectional<br>2.4 GHz: 3 dBi<br>5 GHz: 4 dBi  |
| Plug & Play Mesh Technology | Supported  |

|                               |  |
|-------------------------------|--|
| Wi-Fi standards               | 802.11a/b/g/n/ac   |
| Protection of radio networks  | WEP, WPA-PSK, WPA-Enterprise (WPA / WPA2, TKIP / AES)        |
| BSSID                         | Up to 4 per radio interface (total up to 8 per access point) |
| Fastening                     | Wall / mast / quick change bracket (included)                |
| Operating ambient temperature | -30.. +70 °C   |
| Ambient humidity working      | 5..95% without condensation                                  |