

UAP-AC-PRO

Ubiquiti UniFi AP AC Pro - İstifadə olunan MIMO 3x3 WiFi 5GHz diapazonu üçün 1300 Mb/s və 2,4GHz diapazonu üçün 450 Mb/s məlumat ötürmə sürətini təmin edir.



| | |
|--------------|-------------|
| Model | UAP-AC-PRO |
| Brend | Ubiquiti |
| WIFI | WiFi5 |
| Tezlik | 2.4Ghz/5Ghz |
| Qoşulma sayı | 250+ |
| Mesh | Mesh |
| Genişlik | Dual band |
| PoE | PoE |

Specification

| | |
|---------------------------|----------------------------------------------------------|
| Size | 196.7 x 196.7 x 35 mm |
| Weight | Without fastening 350g With mount 450 g |
| Network interface | 2 ports 10/100/1000 Mbit |
| Ports | 2 RJ45 ports, 1 USB 2.0 port |
| Buttons | Reset to factory settings |
| Antennas | 3 Dual band antennas, 2.4 GHz: 3 dBi, 5 GHz: 3 dBi |
| Wi-Fi standards | 802.11 a/b/g/n/ac |
| Nutrition | Passive PoE 48 V, 803.2at (voltage range: 44 - 57 V DC) |
| Power supply | 48 V, 0.5 A Gigabit PoE power supply, UniFi Switch (PoE) |
| Maximum power consumption | 9 W |
| Maximum transmit power | 22 dBm |
| BSSID | 4 |
| Energy saving | Yes |
| Safety | WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES) |
| Certification | CE, FCC, IC |
| Installation | On the ceiling or wall |
| Working temperature | -10 to 70° C |
| Operating humidity | from 5 to 95% without condensation |
| VLAN | 802.1Q |
| Advanced QoS | Yes |
| Guest Traffic Isolation | Yes |
| WMM | Voice, video, enhanced, background |
| Number of clients | 200+ |

| Communication speed | |
|---------------------|-----------------------------------------------------------|
| 802.11a | 6, 9, 12, 18, 24, 36, 48, 54 Mbit |
| 802.11n | 6.5 Mbit - 450 Mbit (MCS0 - MCS23, HT 20/40) |
| 802.11ac | 6.5 Mbit - 1300 Mbit (MCS0 - MCS9 NSS1/2/3, VHT 20/40/80) |
| 802.11b | 1, 2, 5.5, 11 Mbit |
| 802.11g | 6, 9, 12, 18, 24, 36, 48, 54 Mbit |