

UBIQUITI

UCG-ULTRA

Kod: 00-00005514 · Routerlər



Ubiquiti UniFi Cloud Gateway (UCG-Ultra) ev və kiçik ofislər üçün nəzərdə tutulmuş güclü router-dir. UniFi Controller vasitəsilə mərkəzləşdirilmiş idarəetmə, VPN, firewall və təhlükəsizlik funksiyaları, həmçinin yüksək performanslı şəbəkə idarəetməsi təklif edir. Kompakt dizaynı ilə istifadəsi rahatdır.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)

<https://eurotechnology.az/product/ubiquiti/ucg-ultra>

Texniki göstəricilər



Gateway

Tip



1000 mb/s

Port sürəti



200+

Qoşulma sayı

Ətraflı məlumat

Feature	Specification
Dimensions	141.8 x 127.6 x 30 mm (5.6 x 5 x 1.2")
UniFi Application Suite	Network ✓
Managed UniFi Devices	30+
Simultaneous Users Connected	300+
Max. WAN Port Count	4
Default WAN Ports	(1) 2.5 GbE RJ45
Port Layout	1 GbE RJ45 (4) (1G/100M/10M), 2.5 GbE RJ45 (1) (2.5G/1G/100M/10M)
IDS/IPS Throughput	1 Gbps
Form Factor	Compact desktop
Stateful Firewall	✓
Application-Aware Layer 7 Firewall	✓
DPI & Traffic Identification	✓
Zone-Based Firewall (Regions, Domains, Apps)	✓
Content Filtering	✓
Intrusion Prevention (IPS/IDS)	✓
Ad Blocking	✓
IDS/IPS Signatures	55,000+ with CyberSecure
VLAN/Subnet-based Segmentation	✓
License-Free SD-WAN	✓
Site-to-Site VPN	Site Magic ✓
IPsec	✓
OpenVPN	✓
VPN Server	Identity Endpoint One-Click VPN ✓
Teleport Zero-Config VPN	✓
WireGuard	✓

Feature	Specification
L2TP	✓
VPN Client	OpenVPN ✓, WireGuard ✓
Multi-WAN Load Balancing	✓
Dynamic Routing	OSPF ✓
Advanced QoS	✓
Multicast DNS (mDNS)	✓
Advanced NAT	SNAT / DNAT / Masquerade / NAT Pooling / 1-to-1 NAT
Integrated RADIUS Server	✓
RADIUS over TLS (RadSec)	✓
UniFi LTE Backup Failover	✓
Internet Quality & Outage Reporting	✓
MAC Address Table Size	2,000
Policy-based WAN & VPN Routing	✓
Customizable DHCP Server	✓
IPv6 ISP Support	✓
IGMP Proxy	✓
Max. Power Consumption	6.2W
Power Method	USB type C (5V DC/3A)
Power Supply	USB type C (Adapter included)
Supported Voltage Range	100—240V AC
Processor	Quad-core ARM Cortex-A53 @ 1.5 GHz
System Memory	3 GB
On-board Storage	16 GB
Weight	520 g (1.1 lb)
Enclosure Material	Polycarbonate
LCM Display	0.96" status display
Management	Ethernet, Bluetooth

Feature	Specification
LEDs	Ethernet ✓
Button	(1) Factory-reset
Ambient Temperature	-10 to 40 °C (14 to 104 °F)
Ambient Humidity	5 to 95% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel, SRRC
Application Requirements	Mobile App: UniFi iOS v10.12.0+, UniFi Android v10.11.2+

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az