

UCG-ULTRA

Ubiquiti UniFi Cloud Gateway (UCG-Ultra) ev və kiçik ofislər üçün nəzərdə tutulmuş güclü router-dir. UniFi Controller vasitəsilə mərkəzləşdirilmiş idarəetmə, VPN, firewall və təhlükəsizlik funksiyaları, həmçinin yüksək performanslı şəbəkə idarəetməsi təklif edir. Kompakt dizaynı ilə istifadəsi rahatdır.



Specifications

Model	UCG-ULTRA
Brand	Ubiquiti
Tip	Gateway
Port sürəti	1000 mb/s
Qoşulma sayı	200+

KEY FEATURES

Feature	Specification
Dimensions	141.8 x 127.6 x 30 mm (5.6 x 5 x 1.2")
UniFi Application Suite	Network ❏
Managed UniFi Devices	30+
Simultaneous Users Connected	300+
Max. WAN Port Count	4
Default WAN Ports	(1) 2.5 GbE RJ45
Port Layout	1 GbE RJ45 (4) (1G/100M/10M), 2.5 GbE RJ45 (1) (2.5G/1G/100M/10M)
IDS/IPS Throughput	1 Gbps
Form Factor	Compact desktop
Stateful Firewall	❏
Application-Aware Layer 7 Firewall	❏
DPI & Traffic Identification	❏
Zone-Based Firewall (Regions, Domains, Apps)	❏
Content Filtering	❏
Intrusion Prevention (IPS/IDS)	❏
Ad Blocking	❏
IDS/IPS Signatures	55,000+ with CyberSecure
VLAN/Subnet-based Segmentation	❏
License-Free SD-WAN	❏
Site-to-Site VPN	Site Magic ❏
IPsec	❏
OpenVPN	❏
VPN Server	Identity Endpoint One-Click VPN ❏
Teleport Zero-Config VPN	❏
WireGuard	❏
L2TP	❏
VPN Client	OpenVPN ❏ , WireGuard ❏
Multi-WAN Load Balancing	❏
Dynamic Routing	OSPF ❏
Advanced QoS	❏
Multicast DNS (mDNS)	❏
Advanced NAT	SNAT / DNAT / Masquerade / NAT Pooling / 1-to-1 NAT
Integrated RADIUS Server	❏
RADIUS over TLS (RadSec)	❏
UniFi LTE Backup Failover	❏
Internet Quality & Outage Reporting	❏
MAC Address Table Size	2,000
Policy-based WAN & VPN Routing	❏
Customizable DHCP Server	❏
IPv6 ISP Support	❏

Feature	Specification
IGMP Proxy	☑
Max. Power Consumption	6.2W
Power Method	USB type C (5V DC/3A)
Power Supply	USB type C (Adapter included)
Supported Voltage Range	100—240V AC
Processor	Quad-core ARM Cortex-A53 @ 1.5 GHz
System Memory	3 GB
On-board Storage	16 GB
Weight	520 g (1.1 lb)
Enclosure Material	Polycarbonate
LCM Display	0.96" status display
Management	Ethernet, Bluetooth
LEDs	Ethernet ☑
Button	(1) Factory-reset
Ambient Temperature	-10 to 40 °C (14 to 104 °F)
Ambient Humidity	5 to 95% noncondensing
NDAA Compliant	☑
Certifications	CE, FCC, IC, Anatel, SRRC
Application Requirements	Mobile App: UniFi iOS v10.12.0+, UniFi Android v10.11.2+