

UH500

CUDY UH500 6-IN-1 USB-C Hub 4K HDMI : 1× HDMI 1.4, 4K 30 Hz, 2K 60 Hz 1× Upstream PD USB-C Male (5 Gbps) 4× USB-A 3.2 Gen 1 (5 Gbps) 1× USB-C Receiving 100W PD 48 g (1.69 oz.) 113.1×44.2×15.7 mm (4.45×1.74×0.62")

PC/Mac/iPad/iPhone/Android/Nintendo



Specifications

No technical specifications available.

KEY FEATURES

UH500 1.0

Upstream Connection	1× USB-C 3.2 Gen 1 Male Connector (5 Gbps)
Video Output	1× HDMI 1.4
Video Output Resolutions	<ul style="list-style-type: none"> • 4K (4096×2160) 30 Hz • 2K (2560×1440) 60 Hz • 1080P (1920×1080) 120 Hz
Video Output Modes	<p>Extend, Mirror</p> <p>Android phone supports mirror mode only</p>
USB Ports	4× USB-A 3.2 Gen 1 Ports (5 Gbps)
Power Input	USB-C Port
Power Methods	DC / PD
DC	5~20V 0~5A
Max Power Consumption (W)	<p>100W if powered by a PD Adapter</p> <p>10W if powered by the host client's USB Power</p>
Idle Power Consumption (W)	0.4W
Color	Silver Gray Color
Casing	<ul style="list-style-type: none"> • Aluminum • ABS
Hardware Requirement	Requires a USB-C 3.2 Gen 1 / USB4 / Thunderbolt 3/4 port on the host device
Compatible OS	<ul style="list-style-type: none"> • Windows 7 or later • macOS 10.12 or later • Ubuntu LTS 18.04 or later • Android 5 or higher • iPadOS • iOS
Driver Installation	Driver Free
Environment	<ul style="list-style-type: none"> • Operating Temperature: 0~40 °C (-32~104 °F) • Storage Temperature: -20~70 °C (-10~158 °F) • Operating Humidity: 20~85% RH non-condensing • Storage Humidity: 10~90% RH non-condensing
Product Weight	48 g (1.69 oz.)
Dimension	<p>Main Part :</p> <p>113.1×44.2×15.7 mm</p> <p>4.45×1.74×0.62 inches</p> <p>Cable:</p> <p>167 mm</p> <p>6.57 inches</p>
Retail Package Weight	116 g (4.09 oz.)
Retail Package Dimension	<p>163.5×88.5×20 mm</p> <p>6.44×3.48×0.79 inches</p>
Carton Net Weight	11.6 kg (25.57 lbs)

Carton Gross Weight	12.7 kg (28 lbs)
Carton Dimension	34.5×28.5×36.2 cm 13.58×11.22×14.25 inches