

UHO-B2D-M3F3D

Wifi kamera Uho-B2D-M3F3D, 3MP, 20m, Smart Light, Two Way Talk (İkitərəfli səs), 128gb Micro SD, IP67



Specifications

Model	Uho-B2D-M3F3D
Brand	Uniview
Meqapixel	3 MP
Gec? görm? m?saf?si	20m
S?s	İkitərəfli səs
Micro SD	128Gb
Qo?ulma	Wifi
?? mühiti	Outdoor

KEY FEATURES

Uho-B2D-M3F3D

Camera

Sensor 1/3.0", 3.0 megapixel, progressive scan, CMOS

Minimum Illumination Colour: 0.003 lux (F1.6 AGC ON)
0 lux with IR on

Day/Night IR-cut filter with auto switch (ICR)

Shutter Auto/Manual, 1 ~ 1/100000s

Adjustment angle Pan: 0°~360° Tilt: 0°~90°

S/N >52dB

WDR DWDR

Lens

Lens Type 2.8mm@F1.6

Iris Fixed

Field of View (H) 97.5°

Field of View (V) 52.9°

Field of View (D) 108.0°

DORI

DORI Distance	Lens	Detect(m)	Observe(m)	Identify(m)
	2.8mm	46.7	18.7	4.7
	4.0mm	66.7	26.7	6.7

Illuminator

IR Range Up to 20m (66ft)

Warm Light Range Up to 10m (33ft)

Wavelength 850nm

IR On/Off Control Auto/Manual

Video

Video Compression Ultra 265, H.265, H.264, MJPEG

H.264 code profile Baseline profile, Main profile, High profile

Frame Rate Main Stream: 3MP (2304*1296), Max 25fps; 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps;
Sub Stream: 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;

Video Bit Rate 128 Kbps~6 Mbps

U-code Support

OSD Up to 4 OSDs

Privacy Mask Up to 4 areas

ROI Up to 8 areas

Video stream Dual streams

Image

White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2

Digital Noise Reduction 2D/3D DNR

Smart IR Support

Flip Normal/Vertical/Horizontal/180°

Dewarping N/A

HLC	N/A
BLC	N/A
Defog	Digital Defog
Events	
Basic Detection	Motion detection, Ultra motion detection, Audio detection, Tampering alarm
General Function	IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication
Audio	
Audio Compression	G.711U, G.711A
Audio Bitrate	64 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 128GB
Network Storage	ANR
Network	
Wi-Fi	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna
Protocols	IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP
Compatible Integration	API , SDK
User/Host	Up to 6 users. 2 user levels: administrator and common user
Client	Uniarch Client Uniarch APP
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above
Interface	
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	Support
Built-in Speaker	Support
WIFI	Support
Network	1 * RJ45 10M/100M Base-TX Ethernet
Video Output	N/A
Certifications	
EMC	CE EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 55035) FCC (FCC 47 CFR part15 B)
RF	FCC ID (FCC CFR 47 part15 C) CE RED (EN 301 489-1, EN 301 489-17, EN 300 328, EN 62311)
Safety	CE LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)
General	
Power	DC 12V±25% Power consumption: Max 5.7W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions (L x W x H)	148 × 78 × 78mm (5.8" × 3.1" × 3.1")
Weight	0.31 kg (0.68 lb)
Material	Metal + Plastic
Working Environment	-30~60℃ (-22°F ~ 140°F) Humidity: ≤95% RH (non-condensing)