

UHO-P1A-M5F4D

Wifi kamera UHOP1A-M5F4D 5MP UNIARCH, Two Way Talk (İkitərəfli səs), 256gb Micro SD, IP66



Specifications

Model	Uho-P1A-M5F4D
Brand	Uniview
Meqapixel	5 MP
Gec? görm? m?saf?si	30m
S?s	İkitərəfli səs
Micro SD	256Gb
Qo?ulma	Wifi
?? mühiti	Outdoor

KEY FEATURES

Camera	Uho-P1A-M5F4D				
Sensor	1/2.7" progressive scan, 5.0 megapixel, CMOS				
Min. Illumination	Colour:0.005 lux (F1.6,AGC ON) 0 lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, shutter time: 1s ~ 1/100000s				
WDR	DWDR				
S/N	>52 dB				
Lens					
Lens type	4mm@F1.6				
Digital Zoom	4				
Iris	Fixed				
Field of View (H)	93.6°				
Field of View (V)	48.9°				
Field of View (D)	98.3°				
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4mm	78.3 (256.8ft)	31.3 (102.7ft)	15.7 (51.4ft)	7.8 (25.7ft)
Illuminator					
IR Range	Up to 30m (98ft)				
Warm Light Range	Up to 10m (33ft)				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video					
Video Compression	Ultra 265, H.265, H.264				
Frame Rate	Main Stream: 5MP (2880*1620), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 25fps; 2MP (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360,Max 30fps;				
Video Bit Rate	128 Kbps~6144 Kbps				
ROI	Up to 8 areas				
Video Stream	Dual streams				
OSD	Up to 2 OSDs				
Privacy Mask	Support				
Image					
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital Noise Reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Flip Vertical/Flip Horizontal/180°				
HLC	N/A				
BLC	N/A				
Defog	Digital Defog				

Events

Basic Detection	Motion detection, Ultra motion detection, Audio detection
Auto tracking	Support
General Function	IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication

Audio**Audio Compression** G.711U,G.711A**Audio Bitrate** 64 Kbps**Two-way Audio** Support**Suppression** Support**Sampling Rate** 8 kHz**Storage****Edge Storage** Micro SD, up to 256 GB**Network Storage** ANR**Network****Wi-Fi** 2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna**Protocols** IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP**Compatible** API**Integration****Client** Uniarch Client
Uniarch APP**Web Browser** Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above**Pan & Tilt****Pan Range** 0° ~ 345°**Pan Speed** 1°/s ~ 40°/s

Preset speed: 40°/s

Tilt Range 0° ~ 90°**Tilt Speed** 1°/s ~ 30°/s

Preset speed: 30°/s

Number of Presets 20**Home Position** Support**Interface****Built-in Mic** Support**Built-in Speaker** Support**Wi-Fi** Support**Network** 1 * RJ45 10M/100M Base-TX Ethernet**Certifications****EMC** CE EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 50130)
FCC (FCC 47 CFR part15 B)**RF** FCC ID (FCC CFR 47 part15 C)
CE RED (EN 301 489-1, EN 301 489-17, EN 300 328, EN 62311)**Safety** CE LVD (EN 62368-1)**Environment** CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)**Protection** IP66 (IEC 60529)**General****Power** DC 12V ± 25%

Power consumption: Max 10.0W

Power Interface Ø 5.5mm coaxial power plug © 2026 Uniview. All rights reserved. | Eurotechnology**Dimensions (Ø x H)** Φ118mm*118mm*199mm (Φ4.6"x 4.6"x 7.8")