

# Uho-P1A-M5F4D

Wifi kamera UHOP1A-M5F4D 5MP UNIARCH, Two Way Talk (İkitərəfli səs), 256gb Micro SD, IP66



Model	Uho-P1A-M5F4D
Brend	Uniview
Meqapixel	5 MP
Gecə görmə məsafəsi	30m
Səs	İkitərəfli səs
Micro SD	256Gb
Internet	Wifi

## Specification

Camera	Uho-P1A-M5F4D				
Sensor	1/2.7" progressive scan, 5.0 megapixel, CMOS				
Min. Illumination	Colour:0.005 lux (F1.6,AGC ON) 0 lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, shutter time: 1s ~ 1/100000s				
WDR	DWDR				
S/N	>52 dB				
Lens					
Lens type	4mm@F1.6				
Digital Zoom	4				
Iris	Fixed				
Field of View (H)	93.6°				
Field of View (V)	48.9°				
Field of View (D)	98.3°				
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4mm	78.3 (256.8ft)	31.3 (102.7ft)	15.7 (51.4ft)	7.8 (25.7ft)
Illuminator					
IR Range	Up to 30m (98ft)				

Warm Light Range	Up to 10m (33ft)
Wavelength	850nm
IR On/Off Control	Auto/Manual
<b>Video</b>	
Video Compression	Ultra 265, H.265, H.264
Frame Rate	Main Stream: 5MP (2880*1620), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 25fps; 2MP (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360,Max 30fps;
Video Bit Rate	128 Kbps~6144 Kbps
ROI	Up to 8 areas
Video Stream	Dual streams
OSD	Up to 2 OSDs
Privacy Mask	Support
<b>Image</b>	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Flip Vertical/Flip Horizontal/180°
HLC	N/A
BLC	N/A
Defog	Digital Defog
<b>Events</b>	
Basic Detection	Motion detection, Ultra motion detection, Audio detection
Auto tracking	Support
General Function	IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication
<b>Audio</b>	
Audio Compression	G.711U,G.711A
Audio Bitrate	64 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	8 kHz
<b>Storage</b>	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
<b>Network</b>	
Wi-Fi	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna
Protocols	IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP
Compatible Integration	API
Client	Uniarch Client Uniarch APP
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above
<b>Pan &amp; Tilt</b>	
Pan Range	0° ~ 345°
Pan Speed	1°/s ~ 40°/s
	Preset speed: 40°/s
Tilt Range	0° ~ 90°
Tilt Speed	1°/s ~ 30°/s
	Preset speed: 30°/s
Number of Presets	20
Home Position	Support
<b>Interface</b>	
Built-in Mic	Support
Built-in Speaker	Support

Wi-Fi	Support
Network	1 * RJ45 10M/100M Base-TX Ethernet
Certifications	
EMC	CE EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 50130) FCC (FCC 47 CFR part15 B)
RF	FCC ID (FCC CFR 47 part15 C) CE RED (EN 301 489-1, EN 301 489-17, EN 300 328, EN 62311)
Safety	CE LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)
Protection	IP66 (IEC 60529)
General	
Power	DC 12V ± 25%
	Power consumption: Max 10.0W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions (Ø x H)	Φ118mm*118mm*199mm (Φ4.6"x 4.6"x 7.8")
Weight	0.53kg (1.17lb)
Working Environment	-30°C ~ 60°C (-22°F to 140°F), Humidity:≤95% RH(non-condensing)
Surge Protection	4KV
Reset Button	Support
LED indicator	1, red/green