UNIVIEW

Uho-P1A-M5F4D

Kod: 00-00004924 · Wifi kamera



Wifi kamera UHOP1A-M5F4D 5MP UNIARCH, Two Way Talk (Ikitərəfli səs), 256gb Micro SD, IP66

Texniki göstəricilər

5 MP
Meqapixel

30m
Gecə görmə məsafəsi

İkitərəfli səs
Səs

256Gb
Micro SD

Wifi
Qoşulma

Outdoor
İş mühiti

Ətraflı məlumat

Camera	Uho-P1A-M5F4D				
Sensor	1/2.7" progressive scan, 5.0 megapixel, CMOS				
Min. Illumination	Colour:0.005 lux (F1.6,AGC ON) 0 lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, shutter time: 1s ~ 1/100000s				
WDR	DWDR				
S/N	>52 dB				
Lens					
Lens type	4mm@F1.6				
Digital Zoom	4				
Iris	Fixed				
Field of View (H)	93.6°				
Field of View (V)	48.9°				
Field of View (D)	98.3°				
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4mm	78.3 (256.8ft)	31.3 (102.7ft)	15.7 (51.4ft)	7.8 (25.7ft)
Illuminator					
IR Range	Up to 30m (98ft)				
Warm Light Range	Up to 10m (33ft)				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video					
Video Compression	Ultra 265, H.265, H.264				

Frame Rate	Main Stream: 5MP (2880*1620), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 25fps; 2MP (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360,Max 30fps;
Video Bit Rate	128 Kbps~6144 Kbps
ROI	Up to 8 areas
Video Stream	Dual streams
OSD	Up to 2 OSDs
Privacy Mask	Support
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Flip Vertical/Flip Horizontal/180°
HLC	N/A
BLC	N/A
Defog	Digital Defog
Events	
Basic Detection	Motion detection, Ultra motion detection, Audio detection
Auto tracking	Support
General Function	IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication
Audio	
Audio Compression	G.711U,G.711A
Audio Bitrate	64 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	8 kHz

Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Network	
Wi-Fi	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna
Protocols	IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP
Compatible Integration	API
Client	Uniarch Client Uniarch APP
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above
Pan & Tilt	
Pan Range	0° ~ 345°
Pan Speed	1°/s ~ 40°/s
	Preset speed: 40°/s
Tilt Range	0° ~ 90°
Tilt Speed	1°/s ~ 30°/s
	Preset speed: 30°/s
Number of Presets	20
Home Position	Support
Interface	
Built-in Mic	Support
Built-in Speaker	Support
Wi-Fi	Support
Network	1 * RJ45 10M/100M Base-TX Ethernet
Certifications	

EMC	CE EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 50130) FCC (FCC 47 CFR part15 B)
RF	FCC ID (FCC CFR 47 part15 C) CE RED (EN 301 489-1, EN 301 489-17, EN 300 328, EN 62311)
Safety	CE LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)
Protection	IP66 (IEC 60529)
General	
Power	DC 12V ± 25%
	Power consumption: Max 10.0W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions (Ø x H)	Φ118mm*118mm*199mm (Φ4.6”x 4.6”x 7.8”)
Weight	0.53kg (1.17lb)
Working Environment	-30°C ~ 60°C (-22°F to 140°F), Humidity:≤95% RH(non-condensing)
Surge Protection	4KV
Reset Button	Support
LED indicator	1, red/green

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az