

UHO-S3E-M3TD

Wifi kamera Uho-S3E-M3TD, 3MP, 10m, Two-Way Talk (İkitərəfli səs), 256gb Micro SD, Uniarch APP



Specifications

Model	Uho-S3E-M3TD
Brand	Uniview
Meqapixel	3 MP
Gec? görm? m?saf?si	10m
S?s	İkitərəfli səs
Micro SD	256Gb
Qo?ulma	Wifi
?? mühiti	Indoor

KEY FEATURES

Uho-S3E-M3

Camera

Sensor 1/3", 3.0 megapixel, progressive scan, CMOS

Minimum Illumination Colour: 0.02 lux (F2.0, AGC ON)
0 lux with IR on

Day/Night IR-cut filter with auto switch (ICR)

Shutter Auto/Manual, 1/4 ~ 1/100000s

WDR DWDR

S/N >52dB

Lens

Lens Type 4.0mm @F2.0

Iris Fixed

Angle of View (H) 80.6°

Angle of View (V) 43.3°

Angle of View (O) 86.4°

Illuminator

IR Range Up to 10m (33ft)

Wavelength 850nm

IR On/Off Control Auto/Manual

Video

Video Compression Ultra 265, H.265, H.264

Frame Rate Main Stream: 3MP (2304*1296), Max 25fps; 2MP (1920*1080), Max 30fps; 720P (1280*720), Max 30fps;
Sub Stream: 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;;

Video Bit Rate 128 Kbps~2048 Kbps

ROI Up to 8 areas

Video Stream Dual streams

OSD Up to 2 OSDs

Privacy Mask Support

Image

White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2

Digital Noise Reduction 2D/3D DNR

Smart IR Support

Flip Normal/Flip Vertical/Flip Horizontal/180°

HLC N/A

BLC N/A

Defog Digital Defog

Events

Basic Detection Human body detection, Motion detection, Audio Detection

Auto tracking Support

General Function IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication

Audio

Audio Compression G.711U,G.711A

Audio Bitrate	64 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	8 kHz
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR
Network	
Wi-Fi	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna
Protocols	IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP
Compatible Integration	API
Client	Uniarch Client Uniarch APP
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above
Pan & Tilt	
Pan Range	0° ~ 355°
Pan Speed	17°/s ~ 50°/s Preset speed: 50°/s
Tilt Range	-15° ~ 90°
Tilt Speed	17°/s ~ 50°/s Preset speed: 50°/s
Number of Presets	20
Home Position	Support
Interface	
Built-in Mic	Support
Built-in Speaker	Support
WIFI	Support
Network	1 * RJ45 10M/100M Base-TX Ethernet
Certifications	
EMC	CE EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 55035) FCC (FCC 47 CFR part15 B)
RF	FCC ID (FCC CFR 47 part15 C) CE RED (EN 301 489-1, EN 301 489-17, EN 300 328, EN 62311)
Safety	CE LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)
General	
Power	DC 5V/1.5A USB type-C interface
Dimensions (Ø x H)	Φ80 x 120mm (Ø3.1" x 4.8")
Weight	0.22kg(0.49lb)
Working Environment	-10~50 (-14°F ~ 122°F) Humidity: ≤95% RH (non-condensing)
Storage Environment	-10~50 (-14°F ~ 122°F) Humidity: ≤95% RH (non-condensing)
Surge Protection	N/A
Reset Button	Support
LED indicator	1, red/blue