UNIVIEW

UPS1200-SEA-CEE

Kod: 00-00005933 · UPS



UNV UPS1200-SEA-CEE, elektrik enerjisi kəsildikdə daxilindəki akkumulyatorlar hesabına avadanlıqlarınızı fasiləsiz işlətməyə davam edən 1200VA (720 Watt) gücündə Line-Interactive UPS cihazıdır. Cihazın ən vacib xüsusiyyəti daxilindəki AVR (Avtomatik Voltaj Tənzimləmə) texnologiyasıdır. Bu funksiya sayəsində şəbəkədən gələn elektrik cərəyanı çox aşağı (məsələn 170V) və ya çox yuxarı (məsələn 260V) olduqda belə, cihaz batareya rejiminə keçmədən gərginliyi standart 220V səviyyəsinə tənzimləyir. Üzərindəki standart CEE (Schuko - Avropa/Azərbaycan tipli) çıxışları sayəsində əlavə keçirici adapterə ehtiyac duymadan kompüter, monitor və ya qeydiyyat cihazlarınızı birbaşa qoşa bilərsiniz.

Texniki göstəricilər

1200VA
Vatt

Interaktiv
Rejim

Tower
Forma

Ətraflı məlumat

	UPS1200-SEA-CEE
Capacity	
Capacity	1200 VA
Input	
Input Voltage	169 VAC to 278 VAC
Input Current	7.5 A
Rated Input Frequency	50 Hz / 60 Hz (Adaptive)
Output	
Output Voltage	198 VAC to 242 VAC
Output Current (Mains Supply)	7.5 A Max
Output Current (Battery Powered)	36 A Max
Output Power (Mains Supply)	700 W Max
Output Power (Battery Powered)	530 W Max
Output Frequency	50 Hz / 60 Hz (Adaptive)
Power Factor	0.6
Switch Time	□ 10 ms
Output Wave	Pure Sine Wave (Main Electricity Mode); Square Wave (Battery Mode)
Battery	
Built-in Battery	Yes
Battery Type	Lead - Acid Battery
Qty.of Battery	12 V, 7 Ah × 2
Charging Current	0.5 - 2 A
Limited Charge Voltage (Boost Charge)	28.4 ± 0.4 V
Limited Charge Voltage (Float Charge)	27.2 ± 0.4 V
Charging Time	4-6 hours recover to 90% capacity
Status Indicator Light	

Battery Powered	Middle indicator is flashing red (every 6 seconds)
Mains Supply	Left indicator is green
Charging while Shutdown	Right indicator is steady yellow
Charging while On	Right indicator is yellow with breathing effect
Alarm Indicator	
Low Power	Alarms one sound every 1 second
Overload	Alarms one sound every 0.5 seconds
Fault	Continuous Alarm
Protection	
Short Circuit	Support
Surge	Support
Overload	Support
Heavy Discharge	Support
Overcharge	Support
Plugs and Sockets	
Input Plug	European Standard
Input Cable Length	1 m (39.37 ft)
Socket	Universal Socket
Number of Output Sockets	4
Structure	
Product Dimensions	312 mm * 122 mm * 195 mm (12.3” * 4.4” * 7.7”)
Packaging Dimensions	403 mm * 223 mm * 295 mm (15.9” * 8.8” * 11.6”)
Casing Material	Iron and Plastic
Appearance Color	Black
Net Weight	8.64 Kg (19.05 lbs)
Weight (Battery Only)	2 Kg (4.4 lbs) * 2
Environment	
Operating Temperature	0 ℃ to 40 ℃ (32 ℉ to 104 ℉)

Operating Humidity	0 to 90% (non-condensing)
Storage Temperature	0 ℃ to 40 ℃ (32 ℉ to 104 ℉)
Storage Humidity	0 to 90% (non-condensing)
Certifications	
Certifications	CE

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az