

UPS600-SEA-CEE

UNV UPS600-SEA-CEE, elektrik enerjisi kəsildikdə avadanlıqlarınızı qoruyan və onlara təhlükəsiz sönmə imkanı yaradan 600VA (360 Watt) gücündə yığcam Line-Interactive UPS cihazıdır. Daxilindəki AVR (Avtomatik Voltaj Tənzimləmə) texnologiyası sayəsində, şəbəkədəki elektrik cərəyanı tez-tez oynadıqda (aşağı düşdükdə və ya yüksəldikdə) birbaşa akkumulyator rejiminə keçmədən gərginliyi tənzimləyir. Bu da həm cihazların ömrünü uzadır, həm də daxili batareyanı qoruyur. Üzərindəki standart CEE (Schuko - Avropa/Azərbaycan tipli) çıxışları sayəsində televizor, kompüter, NVR və ya modem kimi gündəlik cihazlarınızı heç bir əlavə keçirici olmadan asanlıqla UPS-ə qoşa bilərsiniz.



Specifications

Model	UPS600-SEA-CEE
Brand	Uniview
Vatt	600VA
Rejim	Interaktiv
Forma	Tower

KEY FEATURES

	UPS600-SEA-CEE
Capacity	
Capacity	600 VA
Input	
Input Voltage	169 VAC to 278 VAC
Input Current	3.6 A
Rated Input Frequency	50 Hz / 60 Hz (Adaptive)
Output	
Output Voltage	198 VAC to 242 VAC
Output Current (Mains Supply)	3.6 A Max
Output Current (Battery Powered)	36 A Max
Output Power (Mains Supply)	360 W Max
Output Power (Battery Powered)	270 W Max
Output Frequency	50 Hz / 60 Hz (Adaptive)
Power Factor	0.6
Switch Time	≤10 ms
Output Wave	Pure Sine Wave (Main Electricity Mode); Square Wave (Battery Mode)
Battery	
Built-in Battery	Yes
Battery Type	Lead - Acid Battery
Qty.of Battery	12 V, 7 Ah × 1
Charging Current	0.5 - 2 A
Limited Charge Voltage (Boost Charge)	14.2 ± 0.2 V
Limited Charge Voltage (Float Charge)	13.6 ± 0.2 V
Charging Time	4-6 hours recover to 90% capacity
Status Indicator Light	
Battery Powered	Middle indicator is flashing red (every 6 seconds)
Mains Supply	Left indicator is green
Charging while Shutdown	Right indicator is steady yellow
Charging while On	Right indicator is yellow with breathing effect
Alarm Indicator	
Low Power	Alarms one sound every 1 second
Overload	Alarms one sound every 0.5 seconds
Fault	Continuous Alarm
Protection	
Short Circuit	Support
Surge	Support
Overload	Support
Heavy Discharge	Support
Overcharge	Support
Plugs and Sockets	
Input Plug	European Standard
Input Cable Length	1.2 m (47.24 ft)

Socket	Universal Socket
Number of Output Sockets	2
Structure	
Product Dimensions	335 mm * 87 mm * 143 mm (13.2" * 3.4" * 5.6")
Packaging Dimensions	392 mm * 142 mm * 205 mm (15.4" * 5.6" * 8.1")
Casing Material	Iron and Plastic
Appearance Color	Black
Net Weight	4.74 Kg (10.45 lbs)
Weight (Battery Only)	2 Kg (4.4 lbs)
Environment	
Operating Temperature	0 ° to 40 ° (32 ° to 104 °)
Operating Humidity	0 to 90% (non-condensing)
Storage Temperature	0 ° to 40 ° (32 ° to 104 °)
Storage Humidity	0 to 90% (non-condensing)
Certifications	
Certifications	CE