

VIGI C330

TP-LINK VIGI C330 UN 3MP 2.8MM OUTDOOR FULL COLOR BULLET NETWORK CAMERA – 24/7 rəngli görüntü, insan və nəqliyyat aşkarlanması, Smart IR/WDR/3D DNR təkmilləşdirmə, IP67 havaçatmaz korpus, daxili mikrofon, H.265+ sıxışdırma, PoE/12V quraşdırma dəstəyi.



Specifications

Model	VIGI C330
Brand	Tp-Link
Növ	IP
Meqapixel	3 MP
Yıllandırma	LED
Yıllandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Plastik
Çalışma mühiti	Outdoor

KEY FEATURES

CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Minimum Illumination	0.005 Lux; 0 Lux with IR/White Light
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Unified/ Scheduled/ Auto
LENS	
Type	Fixed Focal Lens
Focal Length	2.8/4/6 mm
Aperture	F1.6
FOV	• 2.8 mm: Horizontal FOV: 107.5°, Vertical FOV: 57.2°, Diagonal FOV: 128.7°
	• 4 mm: Horizontal FOV: 84.4°, Vertical FOV: 44.3°, Diagonal FOV: 100.6°
	• 6 mm: Horizontal FOV: 55.1°, Vertical FOV:30.2°, Diagonal FOV: 64°
Lens Mount	M12
DORI Distance	• 2.8 mm: Detect: 52 m (170 ft) Observe: 22 m (71 ft) Recognize: 10 m (34 ft) Identify: 5 m (17 ft)
	• 4 mm: Detect: 70 m (230 ft) Observe: 29 m (96 ft) Recognize: 14 m (46 ft) Identify: 7 m (23 ft)
	• 6 mm: Detect: 100 m (327 ft) Observe: 41 m (136 ft) Recognize: 20 m (65 ft) Identify: 10 m (33 ft)
Angle Adjustment (Manual)	
Range	• Pan: 0° to 360°
	• Tilt: 0° to 90°
	• Rotation: 0° to 360°
ILLUMINATOR	
IR LED	• Quantity: 2
	• Range: 30m
	• Wavelength: 850nm

CAMERA

White LED	• Quantity: 2 • Range: 30m
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
VIDEO	
Max. Resolution	2304 × 1296 • Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
Main Stream	• Resolution:2304x1296, 2048x1280, 1920x1080, 1280x720
Sub-Stream	Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps. • Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps • Resolution:704x576, 640x480, 352x288, 320x240
Bit Rate Control	Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps. CBR, VBR
Video Compression	• Main Stream: H.265+/H.265/H.264+/H.264 • Sub-Stream: H.265/H.264
H.264 Type	High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	• Main Stream: 256 Kbps to 4 Mbps • Sub-Stream: 64 Kbps to 512 Kbps
Image	
Image Settings	• Mirror • Brightness • Contrast • Saturation • Sharpness • Exposure • WDR • White Balance • Prevent Overexposure to Infrared Light • HLC Adjustable by Client Software • Rotation(90°/270°)
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	DWDR
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Audio Communication	N/A
Audio Input	Yes
Audio Output	N/A
Audio Compression	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps (G.711a/m)

NETWORK