

VIGI C330I

TP-LINK VIGI C330I UN 3MP 2.8MM OUTDOOR IR BULLET NETWORK CAMERA TP-Link VIGI C330I UN, 3MP (2304×1296) çözünürlüklə outdoor bullet tipli şəbəkə kamerasıdır. 1/2.8" Progressive Scan CMOS sensor, 2.8mm f/2.2 linza və 30m IR gecə görməsi ilə qaranlıqda belə aydın görüntü təmin edir . O, AI əsaslı insan və nəqliyyat vasitəsi aşkarlanması, həmçinin xətt keçmə, zone daxilolma, obyektin atılması və s. kimi smart detection funksiyaları təklif edir. Video sıxışdırılması H.265+ formatında həyata keçirilir və yaddaş/bant genişliyindən qənaətli istifadə təklif edir . Kamera həm PoE (802.3af/at) həm də 12VDC ilə işləyir və IP67 hava şəraiti müqavimətinə malikdir — istixana, villa və digər çöldə quraşdırmalar üçün idealdır



Specifications

Model	VIGI C330I
Brand	Tp-Link
Növ	IP
Meqapixel	3 MP
Çözünürlük	30 m
İrəli	IR
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Plastik
İstifadə sahəsi	Outdoor

KEY FEATURES

CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Aperture	2.8 mm: F2.2
	4 mm: F2.0
	6 mm: F2.0
Lens	2.8 mm/ 4 mm/ 6 mm
Lens Mount	M12
Minimum Illumination	Color: 0.1 Lux; 0 Lux with IR
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Day/Night/Auto/Schedule-Switch
Digital Noise Reduction	3D DNR
WDR	DWDR
Weatherproof Rating	IP67
IR Working Distance	30m
Viewing Angle	2.8mm: 97.8°/52.9°/117.9°(H/V/D)
	4mm: 82.5°/44.9°/99.3°(H/V/D)
	6mm: 51.9°/28.7°/60°(H/V/D)
LENS	
Type	Fixed Focal Lens
Focal Length	2.8 mm/4 mm/6 mm
Aperture	2.8mm: F2.2
	4mm: F2.0
	6mm: F2.0
FOV	2.8 mm: Horizontal FOV: 97.8° , Vertical FOV: 52.9° , Diagonal FOV: 117.9°
	4 mm: Horizontal FOV: 82.5° , Vertical FOV: 44.9° , Diagonal FOV: 99.3°
	6 mm: Horizontal FOV: 51.9° , Vertical FOV: 28.7° , Diagonal FOV: 60°
Lens Mount	M12

CAMERA

DORI Distance	2.8 mm:
	Detect: 49 m (161 ft)
	Observe: 20 m (67 ft)
	Recognize: 10 m (32 ft)
	Identify: 5 m (16 ft)
	4 mm:
	Detect: 65 m (214 ft)
	Observe: 27 m (89 ft)
	Recognize: 13 m (43 ft)
	Identify: 7 m (21 ft)
	6 mm:
	Detect: 98 m (321 ft)
	Observe: 41 m (134 ft)
	Recognize: 20 m (64 ft)
	Identify: 10 m (32 ft)
Angle Adjustment (Manual)	
Range	Pan: -90° to 90°
	Tilt: -90° to 90°
ILLUMINATOR	
IR LED	Quantity: 2
	Range: 30m
	Wavelength: 850nm
White LED	N/A
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
VIDEO	
Max. Resolution	2304 × 1296
	Frame Rate
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Main Stream	Resolution:
	2304x1296, 2048x1280, 1920x1080, 1280x720
	Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
	Frame Rate
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Sub-Stream	Resolution:
	704x576, 640x480, 352x288, 320x240
	Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
	CBR, VBR
Bit Rate Control	Main Stream: H.265+/H.265/H.264+/H.264
	Sub-Stream: H.265/H.264
Video Compression	
H.264 Type	Main Profile/High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	© 2026 Tp-Link. All rights reserved. Eurotechnology
	Main Stream: 256 Kbps to 4 Mbps
	Sub-Stream: 64 Kbps to 512 Kbps