TP-LINK

VIGI C340I

Kod: 00-00005340 · Kamera



TP-LINK VIGI C340I UN 4MP 4MM OUTDOOR IR BULLET NETWORK CAMERA TP-Link VIGI C340I UN, 4 MP (2688×1520) çözünürlüğünə malik outdoor bullet şəbəkə kamerasıdır. 4 mm böyük diyaframlı linza və yüksək həssas sensor sayəsində gecə və gündüz aydın görüntü təmin edir. 30 m IR gecə görüşü sayəsində tam qaranlıqda belə yüksək aydınlıqla müşahidə imkanı verir. Kamera AI əsaslı insan və nəqliyyat aşkarlanması, xətt keçmə və zonaya daxilolma hadisələrinin tanınması kimi ağıllı funksiyalarla təchiz olunub. Eyni zamanda, aktiv müdafiə sistemi onda səs və işıq siqnalı ilə real-vaxt xəbərdarlıq verə bilir. Video keyfiyyəti Smart IR, WDR və 3D-DNR dəstəyi ilə artırılır və H.265+ sıxışdırma texnologiyası yaddaş və bant genişliyindən qənaətlə istifadə edir. Ayrıca, iki-tərəfli audio (mikrofon + dinamik) imkan verir. PoE (802.3af/at) və 12 V DC enerji variantları ilə quraşdırma asanlaşdırılıb. IP67 hava şəraitinə davamlı metal korpus onu yağış, toz və aşırı şəraitlərdə belə qoruyur. 256 GB microSD kart dəstəyi, PoE, ONVIF uyğunluğu və VIGI tətbiqi/vəbb interfeysi vasitəsilə idarəetmə imkanları ilə, VIGI C340I UN, ev həyətləri, ofislər, mağaza qarşısı və digər açıq hava mühitləri üçün ideal seçimdir.

Texniki göstəricilər

IP Növ	**4 MP** Meqapixel
Mic Mikrofon	**Sabit** Obyektiv
4mm Fokus	**İR** İşıqlandırma
50 m İşıqlandırma məsafəsi	**IP67** Qoruma
Plastik Material	**MicroSD** Yaddaş

Outdoor
İş mühiti

Ətraflı məlumat

CAMERA	
Image Sensor	1/3” Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Minimum Illumination	Color: 0.01 Lux; 0 Lux with IR
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Unified/ Scheduled/ Auto
LENS	
Type	Fixed Focal Lens
Focal Length	2.8 mm/4 mm/6 mm
Aperture	• 2.8 mm: F2. 2 • 4 mm: F2.0 • 6 mm: F2.0
FOV	• 2.8 mm: Horizontal FOV: 88.8°, Vertical FOV: 48.9°, Diagonal FOV: 106.5° • 4 mm: Horizontal FOV: 75.2°, Vertical FOV: 40.8°, Diagonal FOV: 88.3° • 6 mm: Horizontal FOV: 49.8°, Vertical FOV: 27.6°, Diagonal FOV: 57.7°
Lens Mount	M12

CAMERA	
DORI Distance	• 2.8 mm: Detect: 60 m (197 ft) Observe: 25 m (82 ft) Recognize: 12 m (39 ft) Identify: 6 m (20 ft) • 4 mm: Detect: 80 m (262 ft) Observe: 33 m (109 ft) Recognize: 16 m (52 ft) Identify: 8 m (26 ft) • 6 mm: Detect: 120 m (394 ft) Observe: 50 m (164 ft) Recognize: 24 m (79 ft) Identify: 12 m (39 ft)
Angle Adjustment (Manual)	
Range	• Pan: 0° to 360° • Tilt: 0° to 90° • Rotation: 0° to 360°
ILLUMINATOR	
IR LED	• Quantity: 2 • Range: 50m • Wavelength: 850nm
White LED	N/A
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
VIDEO	
Max. Resolution	2560 × 1440

CAMERA	
Main Stream	• Frame Rate 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps • Resolution: 2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720 • Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Sub-Stream	• Frame Rate 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps • Resolution: 640x480, 352x288, 320x240 • Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	• Main Stream: H.265+/H.265/H.264+/H.264 • Sub-Stream: H.265/H.264
H.264 Type	High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	• Main Stream: 256 Kbps to 4 Mbps • Sub-Stream: 64 Kbps to 512 Kbps
Image	

CAMERA	
Image Settings	• Mirror • Brightness • Contrast • Saturation • Sharpness • Exposure • WDR • White Balance • Prevent Overexposure to Infrared Light • HLC Adjustable by Client Software • Rotation(90°/270°)
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	DWDR
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Audio Communication	N/A
Audio Input	Yes
Audio Output	N/A
Audio Compression	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
NETWORK	

CAMERA	
Protocol	• TCP/IP • UDP • ICMP • HTTP • HTTPS • DHCP, DNS, RTSP • NTP • UPnP • SSL/TLS • FTP/SFTP • RTP • IPv4 • IPv6 • ARP
ONVIF	Yes
API	Open Network Video Interface (Profile S)
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Client	VIGI App, VIGI Security Manager, Web UI
Web Browser	• Google Chrome® 57 and above • Firefox® 52 and above • Safari® 11 and above • Microsoft® Edge 91 and above
Cloud	Yes
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
ALARM AND EVENT MANAGEMENT	
Smart Event	• Intrusion Detection • Line-Crossing Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned/Removal Detection • Abnormal Sound Detection • People Detection • Vehicle Detection

CAMERA	
Basic Event	• Motion Detection (Enhanced with Human & Vehicle Classification for more accurate alerts) • Video Tampering Detection • Exception (Illegal Login)
Alarm Linkage	Message Push
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Alarm	N/A
Reset Button	N/A
Power	DC Power Port
On-board Storage	N/A
Built-in Microphone	Yes; Records Anything Going on within a 16.4-ft (5 m) Radius of the Camera
Built-in Speaker	N/A
Audio	N/A
GENERAL	
Operating Temperature	-30–60 °C
Storage Temperature	-40–60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing)
Package Content	• VIGI Network Camera • Quick Start Guide • Waterproof Cable Attachments • Mounting Accessories
Material	Plastic
Net Weight	0.28 Kg
Gross Weight	0.43 Kg
Power Supply	• 12V DC ± 5%, Max. 5 W, 5.5mm Coaxial Power Plug • PoE: 802.3af/at, class 0, Max. 5.5 W
Protection	IP67 Waterproof

CAMERA	
Product Dimensions (L x W x H)	78.50 × 188.03 × 71.55 mm (3.09 × 7.40 × 2.82 in)
Certifications	CE, NTRA, VCCI, BSMI

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az