

# VIGI C340I-W

TP-LINK VIGI C340I-W UN 4MP 4MM OUTDOOR FULL COLOR WIFI BULLET NETWORK CAMERA



## Specifications

Model	VIGI C340I-W
Brand	Tp-Link
Növ	IP
Meqapixel	4 MP
??qland?rma	LED
??qland?rma m?saf?si	30 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	4mm
Qoruma	IP67
Material	Plastik
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

CAMERA

<b>Image Sensor</b>	1/3" Progressive Scan CMOS
<b>Shutter Speed</b>	1/3 to 1/10000 s
<b>Slow Shutter</b>	Yes
<b>Minimum Illumination</b>	0.005 Lux; 0 Lux with IR/white light
<b>Day/Night Mechanism</b>	IR Cut Filter
<b>Day/Night Switch</b>	Unified/ Scheduled/ Auto
<b>LENS</b>	
<b>Type</b>	Fixed Focal Lens
<b>Focal Length</b>	2.8 mm/4 mm/6 mm
<b>Aperture</b>	2.8 mm: F1.6 4 mm: F1.6 6 mm: F1.6
<b>FOV</b>	• 2.8mm: Horizontal FOV: 102.5°, Vertical FOV: 55.2°, Diagonal FOV: 122.1°  • 4mm: Horizontal FOV: 76.3°, Vertical FOV: 40.6°, Diagonal FOV: 90.2°  • 6mm: Horizontal FOV: 50.6°, Vertical FOV: 27.8°, Diagonal FOV: 58.8°
<b>Lens Mount</b>	M12
<b>DORI Distance</b>	• 2.8 mm Detect: 64 m (209 ft) Observe: 27 m (87 ft) Recognize: 13 m (42 ft) Identify: 6 m (21 ft)  • 4 mm Detect: 80 m (262 ft) Observe: 33 m (109 ft) Recognize: 16 m (52 ft) Identify: 8 m (26 ft)  • 6 mm Detect: 128 m (420 ft) Observe: 53 m (175 ft) Recognize: 26 m (84 ft) Identify: 13 m (42 ft)
<b>Angle Adjustment (Manual)</b>	
<b>Range</b>	• Pan: 0° to 360° • Tilt: 0° to 90° • Rotation: 0° to 360°

ILLUMINATOR

CAMERA

IR LED	<ul style="list-style-type: none"> <li>• Quantity: 2</li> <li>• Range: 30m</li> <li>• Wavelength: 850nm</li> </ul>
White LED	<ul style="list-style-type: none"> <li>• Quantity: 2</li> <li>• Range: 30m</li> </ul>
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
<b>VIDEO</b>	
Max. Resolution	2560 X 1440
	<ul style="list-style-type: none"> <li>• Frame Rate</li> </ul>
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Main Stream	<ul style="list-style-type: none"> <li>• Resolution:</li> </ul>
	2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720
	<ul style="list-style-type: none"> <li>• Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.</li> <li>• Frame Rate</li> </ul>
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Sub-Stream	<ul style="list-style-type: none"> <li>• Resolution:</li> </ul>
	640x480, 352x288, 320x240
	<ul style="list-style-type: none"> <li>• Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.</li> </ul>
Bit Rate Control	CBR, VBR
Video Compression	<ul style="list-style-type: none"> <li>• Main Stream: H.265+/H.265/H.264+/H.264</li> <li>• Sub-Stream: H.265/H.264</li> </ul>
H.264 Type	High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	<ul style="list-style-type: none"> <li>• Main Stream: 256 Kbps to 4 Mbps</li> <li>• Sub-Stream: 64 Kbps to 512 Kbps</li> </ul>
Image	
Image Settings	<ul style="list-style-type: none"> <li>• Mirror</li> <li>• Brightness</li> <li>• Contrast</li> <li>• Saturation</li> <li>• Sharpness</li> <li>• Exposure</li> <li>• WDR</li> <li>• White Balance</li> <li>• Prevent Overexposure to Infrared Light</li> <li>• HLC Adjustable by Client Software</li> <li>• Rotation(90°/270°)</li> </ul>
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	DWDR
SNR	≥ 52 dB
image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region