

VIGI C385

TP-LINK VIGI C385 UN 8MP 4MM OUTDOOR FULL COLOR BULLET NETWORK CAMERA TP-Link VIGI C385 UN yüksək performanslı, 8MP (3840×2160) çözünürlüklü bullet tipli şəbəkə kamerasıdır və 24 saat full-color görüntü təmin edir—qaranlıqda belə rəngli video çəkiliş mümkündür. Kamera insan və nəqliyyat vasitələrini tanıma, smart detection (xətt keçmə, zonaya daxilolma, korpus şəxsi tərk etmə, ləş düşmə və s.) kimi AI əsaslı bildiriş sistemləri ilə təchiz olunub . Aktiv müdafiə funksiyası sayəsində səs və işıq siqnalları ilə təhlükələrə qarşı ani reaksiya mümkündür. Video keyfiyyəti Smart IR, True WDR (120dB), 3D-DNR və HLC kimi texnologiyalarla artırılır, H.265+ formatı isə yaddaş və bant genişliyinə qənaət edir. Əlavə funksiyalar arasında iki-tərəfli audio, 30m IR və ağ LED işıqlandırma, PoE/12V DC enerji dəstəyi, microSD kart (512GB) və ONVIF uyğunluğu yer alır. IP67 hava şəraitinə davamlı metal korpus onu çətin mühitlərdə belə qənaətcil edir .



Specifications

Model	VIGI C385
Brand	Tp-Link
Növ	IP
Meqapixel	8 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	30 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	4mm
Qoruma	IP67
Material	Metal
Yaddaş	MicroSD

?? mühiti	Outdoor
-----------	---------

KEY FEATURES

CAMERA	
Image Sensor	1/2.7" Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Minimum Illumination	0.005 Lux; 0 Lux with IR/White light
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Unified/ Scheduled/ Auto
LENS	
Type	Fixed Focal Lens
Focal Length	2.8/4 mm
Aperture	F1.6
FOV	• 2.8 mm: Horizontal FOV: 111.4°, Vertical FOV: 58.8°, Diagonal FOV: 134°
	• 4 mm: Horizontal FOV: 91.5°, Vertical FOV: 46.1°, Diagonal FOV: 109.6°
Lens Mount	M12*P 0.5
DORI Distance	• 2.8 mm Detect: 85 m (278 ft) Observe: 35 m (116 ft) Recognize: 17 m (56 ft) Identify: 8 m (28 ft)
	• 4 mm Detect: 107 m (350 ft) Observe: 44 m (146 ft) Recognize: 21 m (70 ft) Identify: 11 m (35 ft)
Angle Adjustment (Manual)	
Range	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°
ILLUMINATOR	
IR LED	• Quantity: 2
	• Range: 30m
White LED	• Wavelength: 850nm
	• Quantity: 2
Illuminator On/Off Control	• Range: 30m
	Auto/Scheduled/Always on/Always off
VIDEO	
Max. Resolution	3840 X 2160
	• Frame Rate
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
Main Stream	• Resolution: 3840x2160, 2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720
	• Note:

If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
© 2026 Tp-Link. All rights reserved. | Eurotechnology
If 120dB is turned on, the frame rate can only support up to 20fps.

CAMERA	
	• Frame Rate 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
Sub-Stream	• Resolution: 704x576,640x480, 352x288, 320x240
	• Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps. If 120dB is turned on, the frame rate can only support up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	• Main Stream: H.265+/H.265/H.264+/H.264 • Sub-Stream: H.265/H.264
H.264 Type	High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile*
H.265+	Main Stream Supported*
Video Bit Rate	• Main Stream: 256 Kbps to 6 Mbps • Sub-Stream: 64 Kbps to 512 Kbps
Image	
	• Mirror • Brightness • Contrast • Saturation • Sharpness • Exposure • WDR • White Balance • Prevent Overexposure to Infrared Light • HLC Adjustable by Client Software
Image Settings	
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	120 dB
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Audio Communication	Two-Way Audio
Audio Input	Yes
Audio Output	Yes
Audio Compression	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
NETWORK	
Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP, UDP, SSL/TLS
ONVIF	Yes
API	Open Network Video Interface (Profile S)
Simultaneous Live View	3 Main Streams & 3 Sub-Streams