

TP-LINK

VIGI C420I

Kod: 00-00005344 · Kamera



TP-LINK VIGI C420I UN 2MP 2.8MM INDOOR IR TURRET NETWORK CAMERA, modern ofis və qapalı məkanlar üçün nəzərdə tutulmuş premium sinif 4 MP (2560×1440) turret şəbəkə kamerasıdır. Geniş diyaframlı 2.8 mm linza və yüksək həssaslı sensor sayəsində 30 m IR gecə görməsi ilə tam rəngli görüntü təmin edir.

Texniki göstəricilər



IP

Növ



2 MP

Meqapixel



Mic

Mikrofon



Sabit

Obyektiv



2.8mm

Fokus



İR

İşıqlandırma



30 m

İşıqlandırma məsafəsi



Plastik

Material



Indoor

İş mühiti

Ətraflı məlumat

CAMERA	
Image Sensor	1/3" Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Minimum Illumination	Color: 0.01 Lux; 0 Lux with IR Light
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Unified/ Scheduled/ Auto
LENS	
Type	Fixed Focal Lens
Focal Length	2.8/4 mm
Aperture	• 2.8 mm: F2.2 • 4 mm: F2.0
FOV	• 2.8mm: Horizontal FOV: 88.2°, Vertical FOV: 48.7°, Diagonal FOV: 106.5° • 4mm: Horizontal FOV: 75.2°, Vertical FOV: 40.8°, Diagonal FOV: 88.3°
Lens Mount	M12
DORI Distance	• 2.8 mm Detect: 45 m (149 ft) Observe: 19 m (62 ft) Recognize: 9 m (30 ft) Identify: 5 m (15 ft) • 4 mm Detect: 60 m (198 ft) Observe: 25 m (83 ft) Recognize: 12 m (40 ft) Identify: 6 m (20 ft)
Angle Adjustment (Manual)	

CAMERA	
Range	• Pan: 0° to 360° • Tilt: 0° to 85° • Rotate: 0° to 360°
ILLUMINATOR	
IR LED	• Quantity: 1 • Range: 30m • Wavelength: 850nm
White LED	N/A
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
VIDEO	
Max. Resolution	1920 × 1080
Main Stream	• Frame Rate□ 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps • Resolution: 1920x1080, 1280x960, 1280x720 Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Sub-Stream	• Frame Rate□ 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps • Resolution: 704x576, 640x480, 352x288, 320x240 Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	• Main Stream: H.265+/H.265/H.264+/H.264 • Sub-Stream: H.265/H.264
H.264 Type	High Profile
H.264+	Main Stream Supported

CAMERA	
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	• Main Stream: 256 Kbps to 4 Mbps • Sub-Stream: 64 Kbps to 512 Kbps
Image	
Image Settings	• Mirror • Brightness • Contrast • Saturation • Sharpness • Exposure • WDR • White Balance • Prevent Overexposure to Infrared Light • HLC Adjustable by Client Software • Rotation(90°/270°)
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	WDR
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Audio Communication	N/A
Audio Input	Yes
Audio Output	N/A
Audio Compression	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes

CAMERA	
Audio Bit Rate	64 Kbps(G.711 alaw)
NETWORK	
Protocol	• TCP/IP • UDP • ICMP • HTTP • HTTPS • DHCP, DNS, RTSP • NTP • UPnP UDP • SSL/TLS • FTP/SFTP • RTP • RTSP • IPv4 • ARP
ONVIF	Yes
API	Open Network Video Interface (Profile S)
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Client	VIGI App, VIGI Security Manager, Web UI
Web Browser	• Google Chrome® 57 and above • Firefox® 52 and above • Safari® 11 and above • Microsoft® Edge 91 and above
Cloud	Yes
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
ALARM AND EVENT MANAGEMENT	

CAMERA	
Smart Event	• Intrusion Detection • Line-Crossing Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned/Removal Detection • Abnormal Sound Detection • People Detection • Vehicle Detection
Basic Event	• Motion Detection (Enhanced with Human & Vehicle Classification for more accurate alerts) • Video Tampering Detection • Exception (Illegal Login)
Alarm Linkage	Message Push
Linkage Method	N/A
Output Notification	Message Push
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Alarm	N/A
Reset Button	N/A
Power	N/A
On-board Storage	N/A
Built-in Microphone	Yes; Records Anything Going on within a 16.4-ft (5 m) Radius of the Camera
Built-in Speaker	N/A
Audio	N/A
GENERAL	
Operating Temperature	-30-60 °C
Storage Temperature	-40-60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing)

CAMERA	
Package Content	• VIGI Network Camera • Quick Start Guide • Mounting Accessories
Material	Plastic
Net Weight	0.19 Kg
Gross Weight	0.34 Kg
Power Supply	PoE: 802.3af/at, class 0, Max. 5.5 W
Protection	N/A
Product Dimensions (L x W x H)	123 × 123 × 83 mm (4.84 × 4.84 × 3.27 in)
Certifications	CE, NTRA, VCCI, BSMI

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az