TP-LINK

VIGI C540

Kod: 00-00005349 · Kamera



TP-LINK VIGI C540 UN 4MP 4MM OUTDOOR FULL COLOR PT NETWORK CAMERA, açıq hava şəraitində yüksək keyfiyyətli və rəngli video nəzarət təmin edən 4MP çözünürlüklü pan-tilt şəbəkə kamerasıdır. Bu kamera, geniş f/1.6 diyaframlı 4mm sabit linza və yüksək həssasiyyətli 1/3” CMOS sensoru sayəsində 24 saat ərzində, hətta tam qaranlıqda belə, canlı və detallı rəngli görüntülər təqdim edir. İnteqrasiya olunmuş ağ işıqlandırma və IR LED-lər 30 metrə qədər effektiv işıqlandırma məsafəsi təmin edir.

Texniki göstəricilər

IP Növ	**4 MP** Meqapixel
PTZ Obyektiv	**4mm** Fokus
LED İşıqlandırma	**30 m** İşıqlandırma məsafəsi
Mic Mikrofon	**IP66** Qoruma
Plastik Material	**MicroSD** Yaddaş

Outdoor
İş mühiti

Ətraflı məlumat

CAMERA	
Image Sensor	1/3” Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Aperture	4 mm: F1.6
Lens	Fixed focal lens (4 mm)
Lens Mount	M12
Minimum Illumination	Color: 0.005 Lux; 0 Lux with IR/white light
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Unified/ Scheduled/ Auto
Digital Noise Reduction	3D DNR
WDR	DWDR
Weatherproof Rating	IP66
Viewing Angle	(4mm) Horizontal FOV: 80°, Vertical FOV: 43.2°, Diagonal FOV: 94.2°
LENS	
Type	Fixed Focal Lens
Focal Length	4 mm
Aperture	F1.6
FOV	4mm: Horizontal FOV: 79°, Vertical FOV: 43°, Diagonal FOV: 93°
Lens Mount	M12
DORI Distance	4 mm: Detect: 80 m (262 ft) Observe: 33 m (109 ft) Recognize: 16 m (52 ft) Identify: 8 m (26 ft)
PTZ	

CAMERA	
Pan/tilt Range	Pan: 0° to 350°, Tilt: 0° to 120°
Pan/tilt Speed	Pan Speed: Configurable from 1° to 55°/s; Preset Speed: 55°/s Tilt Speed: Configurable from 1° to 40°/s, Preset Speed 40°/s
Manual Control Speed	Configurable from 8° to 35°/s
Presets	300
Patrol Scan	8 patrols, up to 8 presets for each patrol
Power-off Memory	Yes
Park Action	Yes
3D Positioning	Preset, Patrol Scan
Angle Adjustment (Manual)	
Range	Pan: 0° to 348° Tilt: 0° to 120°
ILLUMINATOR	
IR LED	Quantity: 2 Range: 30m Wavelength: 850nm
White LED	Quantity: 2 Range: 30m
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
VIDEO	
Max. Resolution	2560 X 1440
Main Stream	Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720 Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.

CAMERA	
Sub-Stream	Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 640x480, 352x288, 320x240 Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	Main Stream: H.265+/H.265/H.264+/H.264 Sub-Stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	Main Stream: 256 Kbps to 4 Mbps Sub-Stream: 64 Kbps to 512 Kbps
Image	
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance, Prevent Overexposure to Infrared Light, HLC Adjustable by Client Software, Rotation(90°/270°)
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	DWDR
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Audio Communication	Two-Way Audio

CAMERA	
Audio Input	Yes
Audio Output	Yes
Audio Compression	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
NETWORK	
Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
ONVIF	Yes
API	Open Network Video Interface (Profile S)
Simultaneous Live View	Up to 6 Channels
Client	VIGI App, VIGI Security Manager, VIGI NVR, Web
Web Browser	Google Chrome® 57 and above Firefox® 52 and above Safari® 11 and above Microsoft® Edge 91 and above
Cloud	Yes
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
Network Storage	NAS (NFS, SMB/ CIFS)
ALARM AND EVENT MANAGEMENT	
Smart Event	Human & Vehicle Classification, Area Intrusion Detection, Line-Crossing Detection, People Detection, Vehicle Detection, Region Entering Detection, Region Exiting Detection, Object Abandoned Detection, Object Removal Detection
Basic Event	Motion Detection, Video Tampering Detection, Exception (Illegal Login)
Alarm Linkage	Memory Card Video Recording, Message Push, Audible Warning, White Light Flashing
Linkage Method	N/A

CAMERA	
Output Notification	Message Push
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Audio Output	N/A
Alarm	N/A
Reset Button	Yes
Power	DC Power Port
Button	Reset Button
On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, Up to 256 GB
Built-in Microphone	Yes
Built-in Speaker	Yes
Audio	N/A
GENERAL	
Operating Temperature	-30–60 °C
Storage Temperature	-40–60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing)
Package Contents	VIGI Network Camera Quick Start Guide Waterproof Cable Attachments Mounting Accessories
Dimensions(H X W X D)	120 × 172 × 198 mm
Material	Plastic
General Features	Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening
Power Consumption	12V DC: Max 14W PoE: Class 4
Power Supply	12V DC ± 5%, 5.5mm Coaxial Power Plug PoE (802.3af/at, class 4)

CAMERA	
Protection	IP66
Product Dimensions (L x W x H)	120 × 172 × 198 mm
Certifications	CE, RCM, BSMI, VCCI, RoHS, NTRA, KC
VIDEO/IMAGE	
Video Compression	Main stream: H.265+/H.265/H.264+//H.264 Sub-Stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Frame Rate & Resolutions	Main Stream Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720 Sub-Stream Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 640x480, 352x288, 320x240
Max. Resolution	2560 X 1440
Video Streaming	Main Stream Sub-Stream
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance, Prevent Overexposure to Infrared Light, HLC Adjustable by Client Software, Rotation (90°/270°)
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Video Bit Rate	Main Stream: 256 Kbps to 4 Mbps Sub-Stream: 64 Kbps to 512 Kbps
Day/Night Switch	Day/Night/Auto/Schedule-Switch
Privacy Mask	Up to 4 Masks
SMART FEATURE-SET	

CAMERA	
Smart Event	Human & Vehicle Classification, Area Intrusion Detection, Line-Crossing Detection, People Detection, Vehicle Detection, Region Entering Detection, Region Exiting Detection, Object Abandoned Detection, Object Removal Detection
Basic Event	Motion Detection, Video Tampering Detection, Exception (Illegal Login)
Linkage Method	N/A
Region of Interest	1 Region
Alarm Linkage	Memory Card Video Recording, Message Push, Audible Warning, White Light Flashing
Output Notification	Message Push

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az