TP-LINK

VIGI NVR1004H

Kod: 00-00005350 · Videoregistrator



TP-LINK VIGI NVR1004H UN 4 CHANNEL NETWORK VIDEO RECORDER
TP-Link VIGI NVR1004H UN – 4 kanal şəbəkə video qeydiyyatçısı (NVR), kiçik və orta bizneslər üçün yüksək keyfiyyətli nəzarət sistemi təmin edir. Dəstək göstərilən xüsusiyyətlər arasında: 4 kanal IP video giriş, 4K HDMI və VGA çıxışlar eyni zamanda aktivləşdirilə bilər – yüksək keyfiyyətli vizual izləmə üçün. Dekodlaşdırma qabiliyyəti: 2 kanal 8 MP, və ya 4 kanal 4 MP qeydiyyatı üçün uyğun – effektiv resurs bölgüsü ilə maksimum performans . Sıxışdırma texnologiyası: H.265+/H.265/H.264+/H.264 formatları ilə yaddaş və bant genişliyinə qənaət təmin edilir. Giriş / çıxış bant genişliyi: 80 Mb/s giriş və 60 Mb/s çıxış – səmərəli video axını üçün kifayətdir. SATA interfeysi – maksimum 16 TB HDD dəstəyi ilə uzunmüddətli qeydiyyat təmin edilə bilər. Sıx sinxron oynatma (up to 4 kanal) – eyni anda qeyd edilmiş görüntüyə baxmaq imkanı. Smart Detection – hərəkət, AI əsaslı insan/və ya nəqliyyat aşkarlanması və həyəcan hadisələri ilə əlaqədar bildiriş funksiyası ilə dəstəklənir. Avtomatik ilkinqurma funksiyası (Auto Initialize) – IP kameraları və HDD parametrlərini avtomatik tanımaqla quraşdırmanı sürətləndirir. Uzaqdan idarəetmə və monitorinq – Android/iOS VIGI tətbiqi, veb interfeys və VIGI Security Manager ilə mövcuddur. Əlavə interfeyslər: 2 × USB 2.0, 1 × audio giriş/çıxış, 1 × RJ-45 LAN, 1 × DC giriş – geniş aksesuar və monitorinq imkanları . Əməliyyat temperaturu: –10 °C – 55 °C – həm ev, həm iş mühitlərində rahat işləyir. Ölçülər və çəkisi: Kompakt dizayn (246 × 148 × 45 mm), təxminən 0.6 kg – masaüstü və rack montajı üçün uyğundur.

Texniki göstəricilər

NVR
Növ

4 kanal
Kanal sayı

8 MP
Meqapixel

1 HDD
Max HDD sayı

16 TB
Max HDD həcmi

Ətraflı məlumat

Video and Audio	
IP Video Input	4-Channel
Incoming Bandwidth	80 Mbps
Outgoing Bandwidth	60 Mbps
HDMI Output Resolution	1 Channel, Resolution: 3840 ×2160/30Hz, 1920 × 1080/60Hz, 1680× 1050/60Hz, 1440 × 900/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
VGA Output Resolution	1 Channel, Resolution: 1920 × 1080/60Hz, 1680× 1050/60Hz, 1440 × 900/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
Video Output Mode	HDMI/VGA Simultaneous Output
Multi-View Display	1/4
DECODING	
Audio Compression	G.711A/G.711U/G.726
Video Compression	H.265+/H.265/ H.264+/H.264
Record Resolution	8 MP / 5 MP / 4 MP / 3 MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Synchronous Playback	4-Channel
Capability	2-ch @ 8MP, 4-ch @ 4MP
Record Management	
Record Mode	• Manual Recording • Scheduling Recording • Motion Detection Recording
Playback Mode	• Instant Playback • Regular Playback • Tag Playback • Event Playback
Backup Mode	• Regular Backup • Video Clip Backup

Video and Audio	
Playback Function	• Play • Pause • Stop • Fast Forward • Fast Backward • Play By Frame • Full Screen • Video Clip • Export Clip • Digital Zoom • Lock Recording • Audio On/Off
NETWORK	
Protocol	UPnP (Plug and Play), NTP (Network Timing)
Mobile Phone Access	Android, iOS
Web Browser	Chrome (57+), Firefox (52+), Edge (91+)
Interoperability	ONVIF, CGI
External Interface	
Network Interface	1, RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface
USB Interface	2× USB 2.0
Audio Interface	1, Audio In; 1, Audio Out
Alarm In/Out	N/A
Serial Interface	N/A
Power	1× DC Jack
Reset Button	1
Speaker	N/A
eSATA	N/A
HDMI	1
VGA	1
HARD DISK	

Video and Audio	
SATA	1 SATA Interface
Capacity	Up to 16 TB Capacity for Each HDD*
Alarm	
General Alarm	• Motion Detection • Video Tampering • Line-Crossing Detection • Intrusion Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned/Removal Detection • Vehicle Detection • Human Detection • Smart Frame
Anomaly Alarm	• Video Loss • Offline and IP Conflict • Disk Exception • Login Exception
Alarm Linkage	• Recording • White Light Alarm • Buzzer • Log • Audible Alarm
GENERAL	
Storage Temperature	-40–70 °C
Storage Humidity	10%~90% RH Non-Condensing
Package Content	• VIGI Network Video Recorder • Power Adapter • HDD Screws • Mouse • Rubber Feet • Quick Installation Guide
Working Temperature	• NVR: -10–55 °C • Power Adapter: 0–40 °C
Working Humidity	10%~90% RH Non-Condensing

Video and Audio	
Dimensions(W X D X H)	246.2 × 148.2 × 45 mm
External Power Supply	DC 12V/1.5A
Net Weight	0.59 kg
Gross Weight	0.95 kg
Max. Power Consumption	4.25 W (without disk)
Certifications	CE, EAC, UKCA, RCM, Triman, BSMI, VCCI, FCC, IC, HDMI

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az