

VIGI NVR1008H-8MP

TP-LINK VIGI NVR1008H-8MP UN 8 CHANNEL POE NETWORK VIDEO RECORDER, 8 kanal PoE+ dəstəyi ilə təchiz olunmuş şəbəkə video qeydiyyatçısıdır. Bu cihaz, 4K HDMI və VGA çıxışları ilə yüksək keyfiyyətli görüntü təqdim edir və H.265+ sıxışdırma texnologiyası sayəsində yaddaş və bant genişliyinə qənaət edir. 10TB-a qədər SATA HDD dəstəyi ilə uzunmüddətli video saxlama imkanı verir. ONVIF protokolu ilə müxtəlif markalı IP kameralarla uyğun işləyir. VIGI tətbiqi və veb interfeysi vasitəsilə uzaqdan izləmə və idarəetmə mümkündür.



Specifications

Model	VIGI NVR1008H-8MP
Brand	Tp-Link
Növ	NVR
Kanal say?	8 kanal
PoE d?st?yi	PoE
Meqapixel	8 MP
Max HDD say?	1 HDD
Max HDD h?cmi	16 TB

KEY FEATURES

Video and Audio

IP Video Input	8-Channel
Incoming Bandwidth	80 Mbps
Outgoing Bandwidth	60 Mbps
HDMI Output Resolution	1 Channel, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
VGA Output Resolution	1 Channel, Resolution: 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
Video Output Mode	HDMI/VGA Simultaneous Output
Multi-View Display	1/4/6/8
DECODING	
Audio Compression	G.711A/G.711U/G.726
Video Compression	H.265+/H.265/ H.264+/H.264
Record Resolution	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	8-Channel+
Capability	• 25fps: 2-ch @ 8MP, 4-ch @ 4MP, 8-ch @ 2MP
	• 30fps: 4-ch @ 3MP, 2-ch @ 5MP
Record Management	
Record Mode	• Manual Recording
	• Scheduling Recording
Playback Mode	• Motion Detection Recording
	• Instant Playback
	• Regular Playback
	• Tag Playback
Backup Mode	• Event Playback
	• Regular Backup
Playback Function	• Video Clip Backup
	• Play
	• Pause
	• Stop
	• Fast Forward
	• Fast Backward
	• Play By Frame
	• Full Screen
	• Video Clip
	• Export Clip
NETWORK	• Digital Zoom
	• Lock Recording
	• Audio On/Off
Protocol	UPnP (Plug and Play), NTP (Network Timing), SMTP, DNS, TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, RTSP, SSL/TLS, RTP, IPv4, ARP, FTP/SFTP, IPv6, SNMP

Video and Audio

Mobile Phone Access	Android, iOS
Web Browser	Chrome (57+), Firefox (52+), Edge (91+)
Interoperability	ONVIF Profile S, CGI
External Interface	
Network Interface	1 RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface
USB Interface	2× USB 2.0
Audio Interface	1-ch RCA Input; 1-ch RCA Output
Alarm In/Out	N/A
Serial Interface	N/A
Power	1× DC Jack
Reset Button	1
Speaker	N/A
eSATA	N/A
HDMI	1
VGA	1
HARD DISK	
SATA	1 SATA Interface
Capacity	Up to 16 TB Capacity for Each HDD*
PoE	
Standard	802.3at/af Compliant
Interface	1- 8, RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface
PoE Budget	113 W Available for All PoE+ Ports, 30 W Max per Port
Alarm	
General Alarm	• Motion Detection • Video Tampering • Scene Change Detection • Line-Crossing Detection • Intrusion Detection • Region Entering Detection • Region Exiting Detection • Loitering Detection • Object Abandoned/Removal Detection • Vehicle Detection • Human Detection • Abnormal Sound Detection • Smart Frame Note: The alarm function requires the use of a camera.
Anomaly Alarm	• Video Loss • Offline and IP Conflict • Disk Exception • Login Exception • Recording • White Light Alarm
Alarm Linkage	• Buzzer • Log • Audible Alarm Note: The alarm function requires the use of a camera.

GENERAL

Storage Temperature	-40 ° to 70 °C (-40 ° to 158 °F)
Storage Humidity	10% - 90% RH, Non-Condensing