

VIGI NVR4032H

TP-LINK VIGI NVR4032H UN 32 CHANNEL NETWORK VIDEO RECORDER, 32 kanal IP video girişini dəstəkləyən və 8MP-ə qədər yüksək keyfiyyətli görüntüləri qeyd edə bilən şəbəkə video qeydiyyatçısıdır. H.265+ sıxışdırma texnologiyası sayəsində yaddaş və bant genişliyinə qənaət edir. Cihaz, HDMI və VGA çıxışları ilə müxtəlif monitorlara qoşula bilər və eyni anda 16 kanallı canlı görüntü təqdim edir. Uzaqdan idarəetmə üçün VIGI tətbiqi və veb interfeysi mövcuddur, bu da istifadəçilərə istənilən yerdən sistemə nəzarət etməyə imkan verir.



Specifications

Model	VIGI NVR4032H
Brand	Tp-Link
Növ	NVR
Kanal say?	32 kanal
Meqapixel	8 MP
Max HDD say?	4 HDD
Max HDD həcmi	16 TB

KEY FEATURES

Video and Audio

IP Video Input	32-Channel
Incoming Bandwidth	320 Mbps
Outgoing Bandwidth	320 Mbps
HDMI Output Resolution	1 Channel, Resolution: 3840x2160/30Hz,1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA Output Resolution	1 Channel, Resolution: 1920x1080/60Hz,1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Video Output Mode	HDMI and VGA Independent / Simultaneous Output
Multi-View Display	1/4/6/8/9/16/25/32/36

DECODING

Audio Compression	G.711A/G.711U/G.726
Video Compression	H.265+/H.265/ H.264+/H.264
Record Resolution	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	16-Channel† • 25fps: 16-ch@2MP‡32-ch@720P
Capability	 • 30fps: 4-ch@8MP‡6-ch@5MP‡8-ch@4MP

Record Management

Record Mode	• Manual Recording • Scheduling Recording • Motion Detection Recording
Playback Mode	• Instant Playback • Regular Playback • Tag Playback • Event Playback
Backup Mode	• Regular Backup • Video Clip Backup • Play • Pause • Stop • Fast Forward • Fast Backward
Playback Function	• Play By Frame • Full Screen • Video Clip • Export Clip • Digital Zoom • Lock Recording • Audio On/Off

NETWORK

Video and Audio

Protocol UPnP (Plug and Play), NTP (Network Timing), SMTP, DNS, TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, RTSP, SSL/TLS, RTP, IPv4, ARP, IPv6, SNMP

Mobile Phone AccessAndroid, iOS

Web Browser Chrome (57+), Firefox (52+), Edge (91+)

Interoperability ONVIF Profile S, CGI

External Interface

Network Interface 2, RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface

USB Interface 2 Front USB 2.0 Ports, 1 Rear USB 3.0 Port

Audio Interface 1-ch RCA Input; 1-ch RCA Output

Alarm In/Out 16/4

Serial Interface 1, RS232

Power 1× AC Jack

Reset Button 1

Speaker N/A

eSATA N/A

HDMI 1

VGA 1

HARD DISK

SATA 4 SATA Interfaces

Capacity Up to 16 TB Capacity for Each HDD*

Alarm

- General Alarm
- Motion Detection
 - Video Tampering
 - Line-Crossing Detection
 - Intrusion Detection
 - Region Entering Detection
 - Region Exiting Detection
 - Object Abandoned/Removal Detection
 - Vehicle Detection
 - Human Detection
- Note: The alarm function requires the use of a camera.

- Anomaly Alarm
- Video Loss
 - Offline and IP Conflict
 - Disk Exception
 - Login Exception
 - Fan Exception

- Alarm Linkage
- Recording
 - White Light Alarm

- Buzzer
- Log
- Audible Alarm

Note: The alarm function requires the use of a camera.

GENERAL

Storage Temperature-40 ℃ to 70 ℃ (-40 ℉ to 158 ℉)

Storage Humidity 10%~90% RH Non-Condensing

- VIGI Network Video Recorder
- Mouse
- Installation Guide

- Package Content
- Power Cord
 - HDD Power Cables
 - HDD Data Cables