TP-LINK

VIGI NVR4032H

Kod: 00-00005355 · Videoregistrator



TP-LINK VIGI NVR4032H UN 32 CHANNEL NETWORK VIDEO RECORDER, 32 kanal IP video girişini dəstəkləyən və 8MP-ə qədər yüksək keyfiyyətli görüntüləri qeyd edə bilən şəbəkə video qeydiyyatçısıdır. H.265+ sıxışdırma texnologiyası sayəsində yaddaş və bant genişliyinə qənaət edir. Cihaz, HDMI və VGA çıxışları ilə müxtəlif monitorlara qoşula bilər və eyni anda 16 kanallı canlı görüntü təqdim edir. Uzaqdan idarəetmə üçün VIGI tətbiqi və veb interfeysi mövcuddur, bu da istifadəçilərə istənilən yerdən sistemə nəzarət etməyə imkan verir.

Texniki göstəricilər

NVR	**32 kanal**
Növ	Kanal sayı
8 MP	**4 HDD**
Meqapixel	Max HDD sayı
16 TB	
Max HDD həcmi	

Ətraflı məlumat

Video and Audio	
IP Video Input	32-Channel
Incoming Bandwidth	320 Mbps
Outgoing Bandwidth	320 Mbps
HDMI Output Resolution	1 Channel, Resolution: 3840x2160/30Hz,1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA Output Resolution	1 Channel, Resolution: 1920x1080/60Hz,1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Video Output Mode	HDMI and VGA Independent / Simultaneous Output
Multi-View Display	1/4/6/8/9/16/25/32/36
DECODING	
Audio Compression	G.711A/G.711U/G.726
Video Compression	H.265+/H.265/ H.264+/H.264
Record Resolution	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	16-Channel†
Capability	• 25fps: 16-ch@2MP□ 32-ch@720P • 30fps: 4-ch@8MP□ 6-ch@5MP□ 8-ch@4MP
Record Management	
Record Mode	• Manual Recording • Scheduling Recording • Motion Detection Recording

Video and Audio	
Playback Mode	• Instant Playback • Regular Playback • Tag Playback • Event Playback
Backup Mode	• Regular Backup • Video Clip Backup
Playback Function	• Play • Pause • Stop • Fast Forward • Fast Backward • Play By Frame • Full Screen • Video Clip • Export Clip • Digital Zoom • Lock Recording • Audio On/Off
NETWORK	
Protocol	UPnP (Plug and Play), NTP (Network Timing), SMTP, DNS, TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, RTSP, SSL/TLS, RTP, IPv4, ARP, IPv6, SNMP
Mobile Phone Access	Android, iOS
Web Browser	Chrome (57+), Firefox (52+), Edge (91+)
Interoperability	ONVIF Profile S, CGI
External Interface	
Network Interface	2, RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface
USB Interface	2 Front USB 2.0 Ports, 1 Rear USB 3.0 Port
Audio Interface	1-ch RCA Input; 1-ch RCA Output
Alarm In/Out	16/4
Serial Interface	1, RS232
Power	1× AC Jack

Video and Audio	
Reset Button	1
Speaker	N/A
eSATA	N/A
HDMI	1
VGA	1
HARD DISK	
SATA	4 SATA Interfaces
Capacity	Up to 16 TB Capacity for Each HDD*
Alarm	
General Alarm	• Motion Detection • Video Tampering • Line-Crossing Detection • Intrusion Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned/Removal Detection • Vehicle Detection • Human Detection Note: The alarm function requires the use of a camera.
Anomaly Alarm	• Video Loss • Offline and IP Conflict • Disk Exception • Login Exception • Fan Exception
Alarm Linkage	• Recording • White Light Alarm • Buzzer • Log • Audible Alarm Note: The alarm function requires the use of a camera.
GENERAL	
Storage Temperature	-40 ℃ to 70 °C (-40 ℉ to 158 ℉)

Video and Audio	
Storage Humidity	10%~90% RH Non-Condensing
Package Content	• VIGI Network Video Recorder • Mouse • Installation Guide • Power Cord • HDD Power Cables • HDD Data Cables • Terminal Blocks • Mounting Brackets • Screws • Rubber Feet • HDD Screws
Working Temperature	NVR: -10 ℃ to 55 °C (14 ℉ to 131 ℉)
Working Humidity	10%~90% RH Non-Condensing
Dimensions(W X D X H)	17.3 × 13 × 1.7 in (440 × 330 × 44 mm)
External Power Supply	100-240 VAC, 50 to 60HZ, 1.5A
Net Weight	4.0 Kg§
Gross Weight	5.2 Kg§
Power Supply	100-240 VAC, 50 to 60HZ, 1.5A
Max. Power Consumption	• 5 W (Without Disk) • 48 W (With Disk)
Certifications	CE, EAC, UKCA, RCM, Triman, RoHS, VCCI, FCC, IC, HDMI

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az