

TP-LINK

VIGI NVR4064H

Kod: 00-00005356 · Videoregistrator



TP-LINK VIGI NVR4064H UN 64 CHANNEL NETWORK VIDEO RECORDER, 64 kanal IP video girişini dəstəkləyən və 8MP-ə qədər yüksək keyfiyyətli görüntüləri qeyd edə bilən şəbəkə video qeydiyyatçısıdır. H.265+ sıxışdırma texnologiyası sayəsində yaddaş və bant genişliyinə qənaət edir. Cihaz, HDMI və VGA çıxışları ilə müxtəlif monitorlara qoşula bilər və eyni anda 16 kanallı canlı görüntü təqdim edir. Uzaqdan idarəetmə üçün VIGI tətbiqi və veb interfeysi mövcuddur, bu da istifadəçilərə istənilən yerdən sistemə nəzarət etməyə imkan verir.

Texniki göstəricilər

**NVR**

Növ

**64 kanal**

Kanal sayı

**8 MP**

Meqapixel

**4 HDD**

Max HDD sayı

**16 TB**

Max HDD həcmi

Ətraflı məlumat

Video and Audio	
IP Video Input	64-Channel
Incoming Bandwidth	Default: 260Mbps Extended Bandwidth Mode: 320Mbps
Outgoing Bandwidth	Default: 180Mbps Extended Bandwidth Mode: 320Mbps
HDMI Output Resolution	2 Channels - HDMI1 Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz - HDMI2 Resolution: 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
VGA Output Resolution	1 Channel, Resolution: 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
Video Output Mode	- HDMI1 and HDMI2 Independent / Simultaneous Output - HDMI1 and VGA Independent / Simultaneous Output Note: HDMI2 and VGA cannot operate simultaneously. If both connections are made, HDMI2 will take precedence and function as the primary output.
Multi-View Display	1,4,6,8,9,16,25,32,36,49,64
DECODING	
Audio Compression	G.711A/G.711U/G.726
Video Compression	H.265+/H.265/ H.264+/H.264
Record Resolution	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	16-Channelf
Capability	25fps: 16-ch@2MP □ 32-ch@720P □ 64-ch@D1 30fps: 4-ch@8MP □ 6-ch@5MP □ 8-ch@4MP
Record Management	

Video and Audio	
Record Mode	• Manual Recording • Scheduling Recording • Motion Detection Recording
Playback Mode	• Instant Playback • Regular Playback • Tag Playback • Event Playback
Backup Mode	• Regular Backup • Video Clip Backup
Playback Function	• Play • Pause • Stop • Fast Forward • Fast Backward • Play By Frame • Full Screen • Video Clip • Export Clip • Digital Zoom • Lock Recording • Audio On/Off
NETWORK	
Protocol	UPnP (Plug and Play), NTP (Network Timing), SMTP, DNS, TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, RTSP, SSL/TLS, RTP, IPv4, ARP, IPv6, SNMP
Mobile Phone Access	Android, iOS
Web Browser	Chrome (57+), Firefox (52+), Edge (91+)
Interoperability	ONVIF Profile S, CGI
External Interface	
Network Interface	2, RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface
USB Interface	2 Front USB 2.0 Ports, 1 Rear USB 3.0 Port
Audio Interface	1-ch RCA Input; 1-ch RCA Output
Alarm In/Out	16/4

Video and Audio	
Serial Interface	1, RS232
Power	1× AC Jack
Reset Button	1
Speaker	N/A
eSATA	1
HDMI	2
VGA	1
HARD DISK	
SATA	4 SATA Interfaces
Capacity	Up to 16 TB Capacity for Each HDD*
Alarm	
General Alarm	• Motion Detection • Video Tampering • Scene Change Detection • Line-Crossing Detection • Intrusion Detection • Region Entering Detection • Region Exiting Detection • Loitering Detection • Object Abandoned/Removal Detection • Vehicle Detection • Human Detection • Abnormal Sound Detection • Smart Frame Note: The alarm function requires the use of a camera.
Anomaly Alarm	• Video Loss • Offline and IP Conflict • Disk Exception • Login Exception • Fan Exception

Video and Audio	
Alarm Linkage	• Recording • White Light Alarm • Buzzer • Log • Audible Alarm Note: The alarm function requires the use of a camera.
GENERAL	
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Storage Humidity	10%~90% RH Non-Condensing
Package Content	• VIGI Network Video Recorder • Mouse • Installation Guide • Power Cord • HDD Power Cables • HDD Data Cables • Terminal Blocks • Mounting Brackets • Screws • Rubber Feet • HDD Screws
Working Temperature	NVR: -10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10%~90% RH Non-Condensing
Dimensions(W X D X H)	17.32 × 12.99 × 1.73 in (440 × 330 × 44 mm)
Net Weight	4.0 Kg#
Gross Weight	5.0 Kg#
Power Supply	100-240 VAC, 50 to 60Hz, 1.5A
Max. Power Consumption	• 6.95 W (Without Disk) • 48.38 W (With Disk)
Certifications	CE, NTRA, KC, HDMI, FCC, IC, VCCI, BSMI, ONVIF