

VIGI NVR4064H

TP-LINK VIGI NVR4064H UN 64 CHANNEL NETWORK VIDEO RECORDER, 64 kanal IP video girişini dəstəkləyən və 8MP-ə qədər yüksək keyfiyyətli görüntüləri qeyd edə bilən şəbəkə video qeydiyyatçısıdır. H.265+ sıxışdırma texnologiyası sayəsində yaddaş və bant genişliyinə qənaət edir. Cihaz, HDMI və VGA çıxışları ilə müxtəlif monitorlara qoşula bilər və eyni anda 16 kanallı canlı görüntü təqdim edir. Uzaqdan idarəetmə üçün VIGI tətbiqi və veb interfeysi mövcuddur, bu da istifadəçilərə istənilən yerdən sistemə nəzarət etməyə imkan verir.



Specifications

Model	VIGI NVR4064H
Brand	Tp-Link
Növ	NVR
Kanal say?	64 kanal
Meqapixel	8 MP
Max HDD say?	4 HDD
Max HDD həcmi	16 TB

KEY FEATURES

Video and Audio

IP Video Input	64-Channel
Incoming Bandwidth	Default: 260Mbps Extended Bandwidth Mode: 320Mbps
Outgoing Bandwidth	Default: 180Mbps Extended Bandwidth Mode: 320Mbps
HDMI Output Resolution	2 Channels • HDMI1 Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz • HDMI2 Resolution: 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
VGA Output Resolution	1 Channel, Resolution: 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz • HDMI1 and HDMI2 Independent / Simultaneous Output • HDMI1 and VGA Independent / Simultaneous Output
Video Output Mode	Note: HDMI2 and VGA cannot operate simultaneously. If both connections are made, HDMI2 will take precedence and function as the primary output.
Multi-View Display	1,4,6,8,9,16,25,32,36,49,64
DECODING	
Audio Compression	G.711A/G.711U/G.726
Video Compression	H.265+/H.265/ H.264+/H.264
Record Resolution	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	16-Channel† • 25fps: 16-ch@2MP∕32-ch@720P∕64-ch@D1
Capability	• 30fps: 4-ch@8MP∕6-ch@5MP∕8-ch@4MP
Record Management	
Record Mode	• Manual Recording • Scheduling Recording • Motion Detection Recording
Playback Mode	• Instant Playback • Regular Playback • Tag Playback • Event Playback
Backup Mode	• Regular Backup • Video Clip Backup

Video and Audio

Playback Function	• Play
	• Pause
	• Stop
	• Fast Forward
	• Fast Backward
	• Play By Frame
	• Full Screen
	• Video Clip
	• Export Clip
	• Digital Zoom
	• Lock Recording
	• Audio On/Off
NETWORK	
Protocol	UPnP (Plug and Play), NTP (Network Timing), SMTP, DNS, TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, RTSP, SSL/TLS, RTP, IPv4, ARP, IPv6, SNMP
Mobile Phone Access	Android, iOS
Web Browser	Chrome (57+), Firefox (52+), Edge (91+)
Interoperability	ONVIF Profile S, CGI
External Interface	
Network Interface	2, RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface
USB Interface	2 Front USB 2.0 Ports, 1 Rear USB 3.0 Port
Audio Interface	1-ch RCA Input; 1-ch RCA Output
Alarm In/Out	16/4
Serial Interface	1, RS232
Power	1× AC Jack
Reset Button	1
Speaker	N/A
eSATA	1
HDMI	2
VGA	1
HARD DISK	
SATA	4 SATA Interfaces
Capacity	Up to 16 TB Capacity for Each HDD*
Alarm	
General Alarm	• Motion Detection
	• Video Tampering
	• Scene Change Detection
	• Line-Crossing Detection
	• Intrusion Detection
	• Region Entering Detection
	• Region Exiting Detection
	• Loitering Detection
	• Object Abandoned/Removal Detection
	• Vehicle Detection
	• Human Detection
	• Abnormal Sound Detection
	• Smart Frame
	Note: The alarm function requires the use of a camera.
	• Video Loss
	• Offline and IP Conflict