

TP-LINK**VIGI S345ZI**

Kod: 00-00005329 · Kamera



TP-LINK VIGI InSight S345ZI UN 4MP OUTDOOR IR MOTORIZED VF BULLET NETWORK CAMERA TP-Link VIGI InSight S345ZI UN outdoor bullet şəbəkə kamerası yüksək keyfiyyətli 4 MP (2688×1520) görüntü təqdim edir və motorlu 2.7–13.5 mm varifokal lenslə 5× optik zoom imkanı verir. 60 m IR gecə görmə sayəsində zəif və tam qaranlıqda belə yüksək səviyyədə müşahidə təmin edilir. AI əsaslı Human & Vehicle Classification ilə insan və nəqliyyat vasitələrini dəqiqliklə tanıyır, “Smart Detection” funksiyası isə yalnız real hadisələrə diqqət yetirməyi təmin edir. True WDR (120 dB), Smart IR, 3D DNR və White Balance texnologiyaları sayəsində müxtəlif işıqlandırma şəraitlərində optimal görüntü – həm parlaq, həm də qaranlıq bölgələrdə balanslı görünüş təmin olunur. H.265+ sıxışdırma sayəsində yaddaşa və bant genişliyinə qənaət edilir. IP67 hava keçirməyən və IK10 vandalizmdən qorunan metal korpus onu çətin açıq hava şəraitində belə davamlı edir. Audio və alarm interfeysi, iki tərəfli audio dəstəyi daxil olmaqla, təbliğat/bloklama funksiyasına imkan verir.

Texniki göstəricilər

	IP Növ		4 MP Məqapixel
	Motorized Obyektiv		2.7 - 13.5mm Fokus
	İR İşıqlandırma		60 m İşıqlandırma məsafəsi
	Mic Mikrofon		IP67 Qoruma
	Metal Material		MicroSD Yaddaş



Outdoor

İş mühiti

Ətraflı məlumat

CAMERA	
Image Sensor	1/2.9" Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Minimum Illumination	0.005 Lux; 0 Lux with IR Light
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Unified/ Scheduled/ Auto
LENS	
Type	Motorized Varifocal Lens
Focal Length	2.7-13.5 mm (5X Optical Zoom)
Aperture	F1.6
FOV	2.7-13.5 mm: • Horizontal FOV: 29.6°-102.0° • Vertical FOV: 16.8°-53.8° • Diagonal FOV: 34.1°-122.8°
Lens Mount	Φ14
DORI Distance	2.7-13.5 mm: • Detect: 66-207 m (217-579 ft) • Observe: 28-86 m (92-282 ft) • Recognize: 13-41 m (43-135 ft) • Identify: 7-21 m (23-69 ft)
Angle Adjustment (Manual)	
Range	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°
ILLUMINATOR	
IR LED	• Quantity: 4 • Range: 60m (197ft) • Wavelength: 850nm
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
VIDEO	

CAMERA	
Max. Resolution	2688 x 1520
Main Stream	• Frame Rate□ 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps • Resolution: 2688x1520, 2560x1440, 2304x1296, 2048x1280, 1920x1080 - Note: • If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Sub-Stream	• Frame Rate□ 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps • Resolution: 1280x720, 848x480, 704x576, 640x480, 640x360, 352x288, 320x240 • Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	• Main Stream: H.265+/H.265/H.264+/H.264 • Sub-Stream: H.265/H.264
H.264 Type	High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	• Main Stream: 256 Kbps to 6 Mbps • Sub-Stream: 512 Kbps to 1024 Kbps
Image	

CAMERA	
Image Settings	• Mirror • Brightness • Contrast • Saturation • Sharpness • Exposure • WDR • White Balance • Prevent Overexposure to Infrared Light • HLC Adjustable by Client Software
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	120 dB
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Audio Communication	One-Way Audio
Audio Input	Yes
Audio Output	Yes
Audio Compression	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
NETWORK	
Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
ONVIF	Yes
API	Open Network Video Interface (Profile S/T/G)

CAMERA	
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Client	VIGI App, VIGI Security Manager, Web UI, VIGI VMS, VIGI Cloud VMS
Web Browser	• Google Chrome® 57 and above • Firefox® 52 and above • Safari® 11 and above • Microsoft® Edge 91 and above
Cloud	Yes
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
ALARM AND EVENT MANAGEMENT	
Smart Event	• Intrusion Detection • Line-Crossing Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned Detection • Object Removal Detection • Loitering Detection • People Detection • Vehicle Detection • Abnormal Sound Detection • Scene Change Detection
Basic Event	• Motion Detection (Enhanced with Human & Vehicle Classification for more accurate alerts) • Video Tampering Detection • Exception (Illegal Login)
Alarm Linkage	• Memory Card Video Recording • Message Push • Audible Warning • Email Alarm • Upload Capture to FTP • Alarm Out Device
Linkage Method	N/A

CAMERA	
Output Notification	• Message Push • Email Alarm • Upload Capture to FTP
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Alarm	1 Alarm In, 1 Alarm Out
Reset Button	Yes
Power	DC Power Port
On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, up to 512 GB*
Built-in Microphone	Yes; Records Anything Going on within a 16.4-ft (5 m) Radius of the Camera
Built-in Speaker	N/A
Audio	1 Audio In, 1 Audio Out
GENERAL	
Operating Temperature	-30~60 °C
Storage Temperature	-40~60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing)
Package Content	• VIGI Network Camera • Quick Start Guide • Waterproof Cable Attachments • Mounting Accessories
Material	Metal
Net Weight	Kg
Gross Weight	Kg
Power Supply	• 12V DC $\pm$ 5%, Max.10.8 W, 5.5 mm Coaxial Power Plug • PoE: 802.3af/at, class 0, Max.12 W
Protection	IP67 Weatherproof, IK10 Vandal Proof
Product Dimensions (L x W x H)	10.1 x 3.9 x 4 in (256 x 100 x 101 mm)

CAMERA**Certifications**

CE, NTRA, VCCI, KC, BSMI, FCC, IP67, IK10, ONVIF

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az