

# VTO1000J

Dahua domofon analoq VTO1000J qapı zəngi; 1.3 MP; Bucaq - 70°; DWDR; IP66; Gümüşü; Plastik;



|               |          |
|---------------|----------|
| Model         | VTO1000J |
| Brend         | Dahua    |
| Bağlantı tipi | Analoq   |
| Cihaz         | Zəng     |
| Material      | Plastik  |

## Specification

|                       |  |
|-----------------------|--|
| System                |  |
| Button Type           | Mechanical   |
| Basic                 |  |
| Camera                | 1.3MP CMOS   |
| Field of View         | Horizontal: 70°<br>Vertical: 40°                   |
| WDR                   | DWDR   |
| Illuminator Type      | Auto IR  |
| Day/Night             | ICR auto switch                                    |
| Audio Input           | 1 channel to the microphone; pickup distance 0.5 m |
| Audio Output          | 1 channel to the speaker                           |
| Status Indicator      | 1 indicator light<br>Green: Power on               |
| Function              |  |
| Communication Mode    | Analog   |
| Unlock Mode           | Local unlock                                       |
| Performance           |  |
| Casing                | PC + ABS   |
| Port                  |  |
| Exit Button           | 1  |
| Door Status Detection | 1  |
| General               |  |
| Color                 | Silver   |
| Power Supply          | Powered by indoor monitor                          |
| Installation          | Surface mount                                      |
| Certifications        | CE/FCC   |

|                              |  |
|------------------------------|--|
| <b>Accessory</b>             | <b>Rain cover (included)</b>   |
| <b>Dimensions</b>            | 131.45 mm × 46.00 mm × 33.80 mm<br>(5.18" × 1.81" × 1.33")   |
| <b>Protection Grade</b>      | IP66 (Apply silicon sealant to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.) |
| <b>Operating Temperature</b> | -30°C to +60°C (-22°F to +140°F)   |
| <b>Operating Humidity</b>    | 10%RH–95%RH  |
| <b>Power Consumption</b>     | ≤ 1W (standby)<br>≤ 3W (working)   |
| <b>Net Weight</b>            | 0.18 kg (0.40 lb)  |
| <b>Gross Weight</b>          | 0.38 kg (0.84 lb)  |