DAHUA

VTO2101E-P-S2

Kod: 00-00004063 · Domofon



Dahua domofon IP VTO2101E-P-S2 qapı zəngi; 2 MP; Bucaq - 80°; 120dB; IP65 IK10; Qara; Metal; PoE;

Texniki göstəricilər

IP Bağlantı tipi	**Zəng** Cihaz
PoE PoE	**SD Card** Yaddaş
Metal Material	

Ətraflı məlumat

System	
Main Processor	Embedded Processor
Button Type	Mechanical
Interoperability	ONVIF; CGI
Network Protocol	RTSP; DNS; P2P; UPnP; RTP; RTMP; SIP; SSH; HTTP/HTTPS; ONVIF
Basic	
Camera	1/2.8" 2-MP CMOS HD Camera
Field of View	H: 80°; V: 40°; D: 90°
WDR	120 dB
Noise Reduction	3D NR; 2D NR
Video Compression	H.264; H.265
Video Resolution	Main stream: 720p, WVGA, D1, and CIF; Sub stream: 1080p, WVGA, D1, QVGA, and CIF
Video Frame Rate	PAL: 25 fps NTSC: 30 fps
Video Bit Rate	768 kbps–8 Mbps
Light Compensation	Auto IR
Day/Night	Auto(ICR)/Color/B/W; Color/B/W
Audio Compression	G.711a; G.711u; PCM
Audio Input	1
Audio Output	Built-in speaker
Audio Mode	Two-way audio
Audio Enhancement	Echo suppression/digital noise reduction; Echo suppression; Digital noise reduction
Audio Bit Rate	16 kHz, 16 bit
Function	
Communication Mode	Full digital

Unlock Mode	Remote
Leave Videos	Yes (SD card inserted in VTH is needed)
Web Configuration	Yes
Performance	
Casing	Zinc alloy
Port	
RS-485	1
Alarm Input	1
Exit Button	1
Lock Control	1
Network Port	1 × RJ-45 10/100 Mbps Ethernet port
Alarm	
Tamper Alarm	Yes
General	
Appearance color	Grey
Power Supply	12 VDC, 1 A; Standard PoE
Power Adapter	Optional
Installation	Surface Mount
Certifications	CE; FCC
Accessory	Included: Alarm power ribbon cable, rain cover
Product Dimensions	163.0 mm × 73.0 mm × 55.0 mm (6.42" × 2.87" × 2.17")
Protection	IP65 IK10
Operating Temperature	–40 °C to +60 °C (–40 °F to +140 °F)
Operating Humidity	10%–90% (RH), non-condensing
Operating Altitude	0 m–3,000 m (0 ft–9,842.51 ft)
Power Consumption	≤ 2.5 W (standby), ≤ 5 W (working)
Gross Weight	0.8 kg (1.76 lb)

Net Weight	0.3 kg (0.66 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az